




The Core Family

The Core family line offers a rich diversity of technical and aesthetic options. Our 3" fixed square offers 14+ finishes & custom wood choices. A wide range of source/optic selections, 3 ranges of Ambient Dim™ (Warm Dim), 5 beam spreads, and a multitude of driver/control options including TruPhase™ (phase dimming down to 0.1%). Our Core product family is created on platform allowing for a high degree of modification.



Wood Finish Available

PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (CR3D-SF)

Trim

- One-piece die cast aluminum or machined wood trim
- Flangeless includes plaster flange with lip
- 14 color options + custom RAL or wood available
- Flanged or Flangeless

Source / Optics

- 2400K, 2700K, 3000K, 3500K, 4000K
- *AmbientDim*™, RGBW & Tunable White options
- 90 CRI, 55+ R9 Standard 95 CRI 90+R9 Optional
- <2 MacAdam Steps (<2SDCM) for fixed white
- Up to 1862 delivered lumens
(Based on 3000k CCT @ 90+ CRI)
- 5 beamspreads available- 10°, 15°, 24°, 36°, & 50°
- [View Photometry](#)

Housing

-  Compliant to  with Airtight Housing
-  Listed – Damp or wet with shower trim
- Approved for 8 (4-in / 4-out) #12 AWG conductors rated for 90°C through wiring
- IC Rated / Airtight Housing approved for use in direct contact with insulation – Chicago Plenum Available
- Heavy gauge steel for new construction or remodel

Driver

- *TruPhase*™ - Dimming to 0.1% - 120V only
- 0-10, DALI-2, DMX, Lutron or Casambi
- Flicker free to IEEE 1789-2015
- Prewired and integral to housing
- Universal 120-277v

Ordering Codes

PROJECT:

SPECIFIER:

DATE:

TYPE:

QUANTITY:

Ordering Code Example: CR3D-SF-DR-Z-AU-C20-35-24-E2-P16-91A-91L-97L-CP

FIXTURE	APERTURE	TRIM	MOUNTING	SOURCE / WATTS	CCT	BEAM	DRIVER / CONTROL	TRIM FINISH	LENS ACCESSORIES	ACCESSORIES
CR3D-SF										
Core 3" Square Fixed Downlight	DR Deep Regress	Flangeless Trims Z Flangeless Trim ZS Flangeless Shower Trim Flanged Trims FS Flanged Shower Trim F Flanged Trim * Aperture Lens Required	Shallow Housing ASPM Airtight Shallow Panel IC-Rated ASP Airtight Shallow Plaster IC-Rated ASU Airtight Shallow Universal IC-Rated   Supports California Title 24 compliance to JA8 Requirements	C6 *   6W 364Lm 90+CRI, 60+R9 C8 *   8W 497Lm 90+CRI, 60+R9 C10 *   10W 580Lm 90+CRI, 60+R9 C14   15W 1397Lm 90+CRI, 60+R9 C20   21W 1862Lm 90+CRI, 60+R9 Tunable T9 10W 90+CRI, 60+R9 Tunable White T15 15W 90+CRI, 60+R9 Tunable White RGBW 90+CRI, 60+R9 Ambient Dim™ A14   15W 656Lm 95+CRI, 90+R9   California Title 24 Compliant to JA8 * Only with 10" optic View Photometry	24 2400K 27 2700K 30 3000K 35 3500K 40 4000K Tunable TW1840 1800-4000K Tunable White w/ E1, E2, E3, E4 TW2765 2700-6500K Tunable White w/ E1, E2, E3, E4 RG1280 1200-8000K RGBW Dynamic Color Changing *Requires E2 or E4 Ambient Dim™ 2722 2700-2200K 3019 3000-1900K 3022 3000-2200K	10 Narrow Spot *Only with C6, C8, & C10 15 Spot 24 Narrow Flood 36 Flood 55 Wide Flood	C1 0-10 1.0%, UNV (120-277V) linear C2 ELV/Triac 1.0%, (120V) linear E1 0-10 0.1%, UNV (120-277V) log E2 DALI-2 0.1%, UNV (120-277V) log E3 0-10 0.1%, UNV (120-277V) linear E4^ DMX 0.1%, UNV (120-277V) Universal DMX Driver/Controller RGBW-DMX ^ INCLUDES DMX/RDM COMPATIBLE DRIVER WITH BUILT-IN DECODER - CONTROLLER BY OTHERS (REMOTE ONLY) TR2 0.1%, (120-120V) log TruPhae™ Up to 20W Forward and Reverse compatible Phase Dimming Static White & Ambient Dim only	W White Paint B Black Paint D Wood* PXX Specialty Paint Color* P01-P15 C Custom/RAL Color**  *Wood "D" Selection to be used with Z trim and PM mounting **See Specialty Finish Guide  	Aperture Lens 91A Solite 93A Frosted XXA Other Aperture Lens Treatments* Reflector (lamp) Media 91L Solite 93L Frosted 97L Black Hexcel Louver XXL Other reflector (lamp) media* 1 piece of Media per opening (aperture or reflector) can be selected *Refer to Lens Accessory Guide 	CP Chicago Plenum EM Emergency Pack* *Remote Required Controls ATH Lutron Athena Wireless Node Must be used with E2 driver CA Casambi Wireless BLE to be paired with driver


Ceiling Cutouts and Dimensions

Deep Regress shown - other apertures are similar


Square Flangeless Housing

Panel Mount (Z/ASPM)

CR3D-SF-Z-ASPM-




Panel Mount Detail






Square Flangeless Housing

Plaster Mount (Z/ASP)

CR3D-SF-Z-ASP-




Hanger Bar Detail








Square Flanged Housing

Universal Mount (F/ASU)

CR3D-SF-F-ASU-





Photometric Table All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated flux range.

		10°				15°				24°				36°				50°			
	System watts (W)	Del. Lms	Lms/ Watt	Peak CD	10% Field	Del. Lms	Lms/ Watt	Peak CD	10% Field	Del. Lms	Lms/ Watt	Peak CD	10% Field	Del. Lms	Lms/ Watt	Peak CD	10% Field	Del. Lms	Lms/ Watt	Peak CD	10% Field
Citizen C6	6	364	63	8326	18°	Not Compatible				Not Compatible				Not Compatible				Not Compatible			
Citizen C8	8	497	60	11368	18°																
Citizen C10	10	580	54	13266	18°																
Citizen C14	15	Not Compatible				1297	82	13620	28°	1398	89	7083	41°	1362	87	4162	52°	1368	87	2305	68°
Citizen C20	20					1723	79	18688	28°	1862	85	9535	41°	1802	83	5492	52°	1822	84	3080	68°
Ambient Dim A14 - 3019	15					IN PROCESS															
Ambient Dim A14 - 2722	15																				
Ambient Dim A14 - 3022	15																				
Tunable White - T9	12																				
Tunable White - T15	12																				
RGBW	??																				
	Citizen																				
2700	0.95																				
3000	1.00																				
3500	1.02																				
4000	1.03																				



All Measurements delivered or derived delivered lumens based on 3000K.

Citizen CoB C6, C8, C10, C14, C20


- <3 MacAdam Ellipse (<3 SDCM)



Spectra




Color distortion



AmbientDim™ A14


- <3 MacAdam Ellipse (<3 SDCM)




3000 CCT Full Output



Spectra




CRI: 96.9 (R1-R8)



1850 CCT 5% Output



Spectra



CRI: 92.6 (R1-R8)

