




The Core Family

Welcome to the Core line of fixtures. You will find a rich diversity of technical and aesthetic options including 3 trim apertures, over 14 finishes including custom wood trims, flux and source selections featuring 90+ CRI fixed white and our world class Ambient Dim (Warm Dim), multiple beam spreads and plethora of driver and control choices. The Core downlight is created on a platform allowing a high degree of modification, so if you don't see what you are looking for, just ask. We are here to make your project right.



Deep Regress Shown



PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (CR4D-SA)

Trim

- Flanged or Flangeless
- Flangeless includes plaster flange with lip
- 14 color options + custom RAL or wood available
- One-piece die cast aluminum or machined wood trim

Source / Optics

- Lifetime: L87B3>55,000 hours at 40°C Ambient
- 2400K, 2700K, 3000K, 3500K, 4000
- **AmbientDim™**, RGBW, Tunable White options
- 90 CRI, 60+ R9 Standard- 95 CRI 90+R9 Optional with Ambient Dim
- <2 MacAdam Steps (<2SDCM) for fixed white
- Up to 2100 delivered lumens
- Adjustable to 45° with 360° of rotation
- 4 beamspreads available- 15°, 24°, 40°, and 55°

Housing

- **ETL** **24** Compliant to **JAB** with Airtight Housing
- **CS** **UL** Listed – Damp or wet with shower trim
- Approved for 8 (4-in / 4-out) #12 AWG conductors rated for 90°C through wiring
- IC Rated / Airtight Housing approved for use in direct contact with insulation – Chicago Plenum Available
- Heavy gauge aluminum for new construction or remodel

Driver

- **TruPhase™**, 0-10, DALI-2, DMX, Ecosystem or Wireless Control
- Flicker free to IEEE 1798-2015
- Prewired and integral to housing
- Universal 120-277v

Ordering Codes

PROJECT:

SPECIFIER:

DATE:

TYPE:

QUANTITY:

Ordering Code Example: CR4D-SA-DR-Z-AU-C20-35-24-E2-P16-91A-91L-97L-CP-LR

FIXTURE	APERTURE	TRIM	MOUNTING	SOURCE / WATTS	CCT	BEAM	DRIVER / CONTROL	TRIM FINISH	LENS ACCESSORIES	ACCESSORIES
CR4D-SA										
Core 4" Square Adjustable Downlight	DR Deep Regress OR Open Regress FL Flat (Pin Hole)	Flanged Trims F Flanged Trim FS Flanged Shower Trim* (for mounting choose from Flanged Housings) Flangeless Trims Z Flangeless Trim ZS Flangeless Shower Trim* (for mounting choose from Flangeless Housings) * Aperture Lens Required	Flanged Housings U Universal - Non IC Housing AU Airtight Universal IC-Rated Flangeless Housings P Plaster AP Airtight Plaster IC-Rated PM Panel Mount APM Airtight Panel Mount IC-Rated Shallow Housing ASPM Airtight Shallow Panel IC-Rated ASU Airtight Shallow Universal IC-Rated ASP Airtight Shallow Plaster ●●● Supports CA Title 24 compliance to JA8 requirements * Not compatible with C28 Source	Citizen C14 15W 995Lm** 90+CRI, 60+R9 C20 21W 1326Lm** 90+CRI, 60+R9 C28 30W*† 1857Lm** 90+CRI, 60+R9 Tunable T9 10W 90+CRI, 60+R9 Tunable White T15 15W 90+CRI, 60+R9 Tunable White T20 21W 90+CRI, 60+R9 Tunable White RGBW 90+CRI, 60+R9 Ambient Dim™ A14 15W 656Lm 95+CRI, 90+R9 A20 21W 858Lm 95+CRI, 90+R9 ●●● Supports CA Title 24 compliance to JA8 requirements. * Requires Active Cooling, must be used with NIC housing. Not compatible with L2 and LP drivers. †Does not Meet CA Title 24 with Flat aperture. +EldoLED driver selection required and will be supplied with 2 channel version	24 2400K 30 3000K 35 3500K 40 4000K 27 2700K Tunable TW1840 1800-4000K Tunable White w/ E1, E2, E3, E4 TW2765 2700-6500K Tunable White w/ E1, E2, E3, E4 RG1280 1200-8000K RGBW Dynamic Color Changing *Requires E2 or E4 Ambient Dim™ 2722 2700-2200K *A14 Only 3019 3000-1900K 3022 3000-2200K *A14 Only	15 Spot 24 Narrow Flood 40 Flood 55 Wide Flood	C1 0-10 1.0%, UNV (120-277V) linear C2 ELV/Triac 1.0%, (120V) linear E1 0-10 0.1%, UNV (120-277V) log E2 DALI-2 0.1%, UNV (120-277V) log E3 0-10 0.1%, UNV (120-277V) linear E4^ DMX 0.1%, UNV (120-277V) Universal DMX Driver/Controller RGBW-DMX ^ INCLUDES DMX/RDM COMPATIBLE DRIVER WITH BUILT-IN DECODER - CONTROLLER BY OTHERS LD Digital Ecosystem 1.0%, UNV (120-277V) ECO Hi-Lume SoftOn/Fade-to-Black LDE1 TR2 TruPhase™ 0.1%, (120-120V) log Up to 20W Forward and Reverse compatible Phase Dimming Static White & Ambient Dim only * Not compatible with C28 Source	W White Paint B Black Paint D Wood* PXX Specialty Paint Color* P01-P15 C Custom/RAL Color** *Wood "D" Selection to be used with Z trim and PM mounting **See Specialty Finish Guide FINISH GUIDE LINK WOOD TRIM GUIDE	Aperture Lens 91A Solite 93A Frosted XXA Other Aperture Lens Treatments* Reflector (lamp) Media 91L Solite 93L Frosted 97L Black Hexcel Louver XXL Other reflector (lamp) media* 1 piece of Media per opening (aperture or reflector) can be selected *See Lens Accessory Guide LENS ACCESSORY VISUAL GUIDE LINK	EM Emergency Pack* *Remote Required CP Chicago Plenum Controls LR Lutron Wireless RF PowPak ATH Lutron Athena Wireless Node Must be used with E2 driver CA Casambi Wireless BLE to be paired with driver

Ceiling Cutouts and Dimensions


Deep Regress Shown - other apertures similar

Square Flangeless Housing

Plaster Mount (P/AP)

CR4D-SA-DR-Z-P/AP-


NIC- Universal, Plaster & Panel Mount (U, P, PM) ordering code shown. IC - Universal Airtight, Plaster Airtight & Panel Mount Airtight (AU, AP, APM) are same




Sqaure Flanged Housing

Universal Mount (F/U/AU)

CR4D-SA-DR-F-U/AU-





Hanger Bar Detail



Sqaure Flangeless Housing

Universal Mount (Z/U/AU)


CR4D-SA-DR-Z-U/AU-




Square Flangeless Housing

Panel Mount (PM/APM)

CR4D-SA-DR-Z-PM/APM-



Panel Mount Detail




Ceiling Cutouts and Dimensions

Deep Regress Shown - other apertures similar

Square Flangeless Housing

Airtight Shallow Plaster (ASP)


CR4D-SA-DR-Z-ASP-




Sqaure Flanged Housing

Airtight Shallow Universal (F/ASU)

CR4D-SA-DR-F-ASU-




Hanger Bar Detail




Sqaure Flangeless Housing

Airtight Shallow Universal (Z/ASU)

CR4D-SA-DR-Z-ASU-




NOTE: This option is intended for use with precise and finished cutouts. There is no plaster or finish flange.



Square Flangeless Housing


Airtight Shallow Panel (ASPM)

CR4D-SA-DR-Z-ASPM-







NOTE: This option is intended for use with precise and finished cutouts, usually millwork or wood ceiling. There is no plaster flange.

Panel Mount Detail



Photometric Table All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated flux range. Measurements at 3000 CCT

SQUARE Beamspreads		15°					24°					40°					55°				
Source		System watts (W)	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lms/ Watt	Peak CD	10% Field			
Deep Regress	Citizen C14	15	1068	71	7642	42°	995	66	4174	46°	1037	69	3429	51°	996	66	1402	71°			
	Citizen C20	21	1424	68	10190	40°	1326	63	5562	39°	1382	66	4570	55°	1328	63	1870	73°			
	Citizen C28*	30	1848	62	13223	44°	1857	62	7791	47°	1916	64	6336	54°	1816	61	2556	69°			
	Ambient Dim A14	15	694	46	6220	43°	656	44	3189	44°	656	44	1827	53°	643	43	1028	70°			
Open Regress	Citizen C14	15	1173	78	7776	42°	1091	73	4167	52°	1112	74	2422	66°	1058	71	1357	74°			
	Citizen C20	21	1564	74	10369	41°	1455	69	5559	57°	1482	71	3199	63°	1411	67	1810	76°			
	Citizen C28*	30	2158	72	14306	44°	2008	67	7669	55°	2045	68	4455	67°	1947	65	2496	72°			
	Ambient Dim A14	15	810	54	5857	39°	779	52	3270	56°	779	52	1829	60°	764	51	1058	72°			
Flat (Pin Hole)	Citizen C14	15	829	55	7740	37°	737	49	1436	46°	719	48	2379	51°	661	44	1357	64°			
	Citizen C20	21	1105	53	10321	35°	982	47	5513	42°	958	46	3169	49°	881	42	1808	62°			
	Citizen CZ8*	30	1525	51	14258	32°	1355	45	7604	44°	1322	44	4375	53°	1216	41	2496	59°			
	Ambient Dim A14	15	539	36	4828	36°	479	32	2326	42°	467	31	1301	50°	429	29	689	63°			
CCT Multiplier																					
CCT	Citizen																				
2700	0.95																				
3000	1.00																				
3500	1.02																				
4000	1.03																				
All measurements based on 3000 CCT.																					


All Measurements delivered or derived delivered lumens based on 3000K. ISO CD plots based on Open Regress
Ambient dim at full output. C28 source requires active cooling and must be used with NIC housing.
Flat (Pin Hole) at wider beam angles experience significant beam clipping - refer to PDF report for exact FWHM beam angle.

Color Data

All data is based from goniometer measurements of production representative product. All values can vary +/- 10% from LED manufacturer rated data range. Measurements at 3000 CCT


Citizen Source C14, C20 and C28

- <2 MacAdam Ellipse (<2 SDCM)
- 90+ CRI and RF
- 60+R9, Hue Bin 1




Ambient Dim 3000k to 1900k

- <3 MacAdam Ellipse (<3 SDCM)
- 95+ CRI and RF
- 90+R9, Hue Bin 1
- Follows Black Body Locus through dimming range



3000 CCT Full Output



1850 CCT 5% Output

