







The Core Family

When wall washing and accent/downlighting are needed in the same ceiling space, this 8" on center dual aperture fixture delivers a rich diversity of technical and aesthetic options including field configurable wall wash, adjustable accent light, over 14 finishes including custom wood trims, flux and source selections featuring 90+ CRI fixed white and our world class Ambient Dim (Warm Dim), and a plethora of driver and control choices. The Core Downlight/Wall Wash is created on a platform allowing a high degree of modification, so if you don't see what you are looking for, just ask for it.



Aperture Options



Wood Finish Available
with All apertures options

PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (CR4MDW-SMDL)

Trim

- Wall Wash trim and light engine can be field oriented at 90° increments to wash adjacent or opposite walls
- Individual die cast aluminum or machined wood
- 14 color options + custom RAL or wood available
- Plaster Mount allows installation from below with large plaster flange and lip

Source / Optics

- Wall wash achieves a uniform 3.7:1 ratio from top to bottom of 10' wall
- Downlight/Accent adjustable with 45° tilt and 360° rotation
- Over 1900 lumens delivered in downlight and 1000 in wall wash with and C28 source selection
- <2 MacAdam Steps (<2SDCM) for fixed white
- 90 CRI, 60+ R9 Standard- 95 CRI 90+R9 Optional
- 2400K, 2700K, 3000K, 3500K, 4000K Ambient Dim, RGBW & Tunable White options

Housing

- 3 types of flangeless mounting options
- Heavy gauge aluminum for new construction or remodel
- IC Rated / Airtight Housing approved for use in direct contact with insulation – Chicago Plenum Available
- Approved for 8 (4-in / 4-out) #12 AWG conductors rated for 90°C through wiring

-  Listed – Damp or wet with shower trim

-  Compliant to  with Airtight/IC Housing

Driver

- TruPhase™ Dimming to 0.1% available
- Pre-wired and integral to housing
- Flicker free to IEEE 1789-2015 available with EldoLED and TruPhase™ selections
- TruPhase™, 0-10, DALI-2, DMX, Ecosystem or Wireless Control
- Universal 120-277V

Ordering Codes

PROJECT:

SPECIFIER:

DATE:

TYPE:

QUANTITY:

Ordering Code Example: CR4MDW-SMDL-FL-Z-AU-AWL-C20-35-15-LD-2C-P14-LR

Fixture	Aperture	Trim	Mounting	Configuration	Source / Watts	CCT	Beam	Driver / Control	Circuits	Trim Finish	Lens Accessories	Accessories
CR4MDW-SMDL												
Core 4" Square Double Adjustable Downlight/Wall Wash	DR WW/DL-Deep Recess	Flanged Trims	Flanged Housings	AWL Accent/Wall Wash Left	Citizen	24 2400K	15 Spot	C1 0-10 1.0%, UNV (120-277V) linear	1C 1 Circuit	W White Paint	Aperture Lens	CP Chicago Plenum
	OR WW/DL-Open Recess	F Flanged Trim	U Universal - Non IC	WAL Wall Wash Left/Accent	C14 ●● 15W 1068Lm* 90+CRI, 60+R9	27 2700K	24 Narrow Flood	C2 ELV/Triac 1.0%, (120V) linear	2C 2 Circuit	B Black Paint	91A Solite	EM Emergency Pack
	FL WW/DL-Flat (Pin Hole)	FS Flanged Shower Trim*	AU ●● Universal IC/Airtight*	Wall Wash can be field indexed in 90° increments	C20 ●● 21W 1424Lm* 90+CRI, 60+R9	30 3000K	40 Flood	E1 0-10 0.1%, UNV (120-277V) log		D Wood*	93A Frosted	XXA Other Aperture Lens Treatments*
	Note: Select for accent light aperture type	(for mounting choose from Flanged Housings)	P Plaster - Non IC	Thumbnails shown as RCP	C28 ●● 30W† 1848Lm* 90+CRI, 60+R9	35 3500K	55 Wide Flood	E2 DALI-2 0.1%, UNV (120-277V) log		PXX Specialty Paint Color*	ATH Lutron Athena Wireless Node	LR Lutron Wireless RF PowPak
		Flangeless Trims	AP ●● Plaster IC/Airtight*		T14 90+CRI, 60+R9 Tunable White	40 4000K	Tunable			P01-P15	93L Frosted	Must be used with E2 driver
		Z Flangeless Trim	PM Panel Mount - Non IC		T20 ●● 21W 90+CRI, 60+R9 Tunable White	4000K		E3 0-10 0.1%, UNV (120-277V) linear		C Custom/RAL Color**	91L Solite	CA Casambi Wireless BLE to be paired with driver
		ZS Flangeless Shower Trim*	APM ●● Panel Mount Airtight/IC*		RGBW 90+CRI, 60+R9	4000K		E4^ DMX 0.1%, UNV (120-277V) Universal DMX			97L Black Hexcel Louver	
		(for mounting choose from Flangeless Housings)	California Title 24 Compliant		Ambient Dim™	4000K		Driver/Controller RGBW-DMX ^ INCLUDES DMX/RDM COMPATIBLE DRIVER WITH BUILT-IN DECODER - CONTROLLER BY OTHERS			XXL Other reflector (lamp) media*	
			Cannot be used with C28 source		A14 15W 694Lm 95+CRI, 90+R9	4000K		LD Digital Ecosystem 1.0%, UNV (120-277V) ECO Hi-Lume SoftOn/Fade-to-Black LDE1			FINISH GUIDE LINK	Selections for accent light only
					A20 ●● 21W 858Lm 95+CRI, 90+R9	4000K		TR2 TruPhase™ 0.1%, (120-120V) log			WOOD TRIM GUIDE	1 piece of Media per opening (aperture or reflector) can be selected
				California Title 24 Compliant to JA8 for most downlight cells.	*Requires Active Cooling and not compatible with IC/Airtight housing. Not compatible with L2 and LP drivers.	4000K		Up to 20W Forward and Reverse compatible Phase Dimming Static White & Ambient Dim only			LENS ACCESSORY VISUAL GUIDE LINK	*Refer to Lens Guide
					† Requires Active Cooling and not compatible with IC/Airtight housing. Not compatible with L2 and LP drivers.	4000K		* Not compatible with C28				




Ceiling Cutouts and Dimensions

Wall Wash trim and light engine can be configured, in the field, at 90° increments to wash adjacent or opposite walls. Downlight Deep Recess shown, other apertures similar.

4" Square Flangeless Housing

Plaster Mount (P/AP)



CR4MDW-SMDL-DR-Z-P/A



4" Square Flanged Housing

Flanged Mount (U/AU)



CR4MDW-SMDL-DR-F-U/AU



4" Square Flangeless Housing

Flangeless Mount (U/AU)




CR4MDW-SMDL-DR-Z-U/AU



4" Square Flangeless Housing









Panel Mount (PM/APM)

CR4MDW-SMDL-DR-Z-PM/APM





Photometric Table


Values are based on single aperture fixtures. Calculations will require placing both downlight and wall wash elements (IES files) 8" on center in the desired orientation and configuration. All Measurements are delivered or derived delivered lumens at 3000k. Ambient dim at full output. All values can vary +/-10% from source manufacturer rated flux range.

SQUARE Beamspreads		15°						24°						40°						55°					
Source	System watts (W)	Delivered Lumens (lm)	Lumens/Watt	Peak cd	10% Field	Delivered Lumens (lm)	Lumens/Watt	Peak cd	10% Field	Delivered Lumens (lm)	Lumens/Watt	Peak cd	10% Field	Delivered Lumens (lm)	Lms/Watt	Peak cd	10% Field	Delivered Lumens (lm)	Lms/Watt	Peak cd	10% Field				
Deep Regress	Citizen C14	15	1068	71	7642	42°	995	66	4174	46°	1037	69	3429	51°	996	66	1402	71°							
	Citizen C20	21	1424	68	10190	40°	1326	63	5562	39°	1382	66	4570	55°	1328	63	1870	73°							
	Citizen C28*	30	1848	62	13223	44°	1857	62	7791	47°	1916	64	6336	54°	1816	61	2556	69°							
	Ambient Dim A14	15	694	46	6220	43°	656	44	3189	44°	656	44	1827	53°	643	43	1028	70°							
Open Regress	Citizen C14	15	1173	78	7776	42°	1091	73	4167	52°	1112	74	2422	66°	1058	71	1357	74°							
	Citizen C20	21	1564	74	10369	41°	1455	69	5559	57°	1482	71	3199	63°	1411	67	1810	76°							
	Citizen C28*	30	2158	72	14306	44°	2008	67	7669	55°	2045	68	4455	67°	1947	65	2496	72°							
	Ambient Dim A14	15	810	54	5857	39°	779	52	3270	56°	779	52	1829	60°	764	51	1058	72°							
Flat (Pin Hole)	Citizen C14	15	829	55	7740	37°	737	49	1436	46°	719	48	2379	51°	661	44	1357	64°							
	Citizen C20	21	1105	53	10321	35°	982	47	5513	42°	958	46	3169	49°	881	42	1808	62°							
	Citizen C28*	30	1525	51	14258	32°	1355	45	7604	44°	1322	44	4375	53°	1216	41	2496	59°							
	Ambient Dim A14	15	539	36	4828	36°	479	32	2326	42°	467	31	1301	50°	429	29	689	63°							
CCT Multiplier		   																							
CCT		   																							
All measurements based on 3000 CCT.																									

ISO CD plots based on Open Regress. *C28 source requires active cooling and must be used with NIC housing. Flat (Pin Hole) at wider beam angles experience significant beam clipping - refer to PDF report for exact FWHM beam angle.

SQUARE Wall Wash (CR4WW-SF)			
Source	System watts (W)	Delivered Lumens (lm)	Lumens/Watt
Citizen C14	14	679	49
Citizen C20	21	832	40
Citizen C28*	30	1069	35
Ambient Dim A14	15	461	31
CCT Multiplier			
CCT	Citizen		
2700	0.95		
3000	1.00		
3500	1.02		
4000	1.03		


Values are based on a single head Core 4" square wall wash (CR4WW-SF).
*C28 requires active cooling and NIC housing



Color Data

Citizen Sources for C14, 20 and C28

- <2 MacAdam Ellipse (<2 SDCM)
- 90+ CRI and RF
- 60+R9, Hue Bin 1



Ambient Dim 3000k to 1900k

- <3 MacAdam Ellipse (<3 SDCM)
- 95+ CRI and RF
- 90+R9, Hue Bin 1
- Follows Black Body Locus through dimming range

