Formerly known as 1240AW Recessed Adjustable Multiple Aperture (Cell)

# specialty lighting industries


# The Core Family

Welcome to the Core line of fixtures. The family is filled with a rich diversity of options while keeping classic forms. This member of the family allows multiple combinations of Accent/Downlight and wall wash orientations in the same fixture. If 3 cells are needed in a specific combination, just ask. We can most likely make the modification. With many source, driver, control and finish options, including wood, this wall wash delivers a 3.7:1 uniformity from top to bottom of the wall along with 4 beam spreads in the adjustable downlight.


Key Points




\*See below for all 6 possible configurations/orientations




WAL - WALL WASH/ACCENT LEFT REFLECTED PLAN VIEW




AWR - ACCENT/WALL WASH RIGHT REFLECTED PLAN VIEW




WAR - WALL WASH/ACCENT RIGHT REFLECTED PLAN VIEW



AWS - ACCENT/WALL WASH SIDE REFLECTED PLAN VIEW



WAS - WALL WASH/ACCENT SIDE REFLECTED PLAN VIEW



PROJECT: TYPE:

SPECIFIER: DATE:

# Key Points (CR4MDW-TMCA)

#### Trim

- 14 color options + custom RAL or wood available
- Plaster Mount allows installation from below with large plaster flange and lip
- Individual die cast aluminum or machined wood trim assembled to look as one contiguous multi cell fixture

#### Source / Optics

- Wall wash achieves a uniform 3.7:1 ratio from top to bottom of 10' wall
- Downlight/Accent adjustable with 45° tilt and 360° rotation
- Over 1900 lumens delivered in downlight and 1000 in wall wash with and C28 source selection
- <2 MacAdam Steps (<2SDCM) for fixed white</li>
- 90 CRI, 60+ R9 Standard- 95 CRI 90+R9 Optional
- 2400K, 2700K, 3000K, 3500K, 4000K
   Ambient Dim, Tunable White & RGBW options

#### Housing

- 3 types of flangeless mounting options
- Heavy gauge aluminum for new construction or remodel
- IC Rated / Airtight Housing approved for use in direct contact with insulation – Chicago Plenum Available
- Approved for 8 (4-in / 4-out) #12 AWG conductors rated for 90°C through wiring





### Driver

- Dimming to 0.1% available
- Prewired and integral to housing
- Flicker free to IEEE 1789-2015
- Phase, 0-10, DALI-2, DMX, Ecosystem or Wireless Control
- Universal 120-277v

## Core 4" Rectangular Multiple Adjustable Downlight/Wall Wash - 2 Cell

Formerly known as 1240AW Recessed Adjustable Multiple Aperture (Cell)



# **Ordering Codes**

PROJECT: SPECIFIER:


DATE: TYPE: QUANTITY:

## Ordering Code Example: CR4MDW-TMCA-Z-AU-AWL-C20-35-24-LD-2C-P14-91A

Ordering Code Example: CR4MDW-TMCA-Z-AU-AWL-C20-35-24-LD-2C-P14-91A												
FIXTURE	TRIM	MOUNTING	CONFIGURATIO N	SOURCE / WATTS	ССТ	BEAM	DRIVER / CONTROL	CIRCUITS	TRIM FINISH	LENS ACCESSORIES	ACCESSORIES	
CR4MDW- TMCA												
Core 4" Rectangular Multiple Adjustable Downlight/Wall Wash - 2 Cell	Flangeless Trim Note: Open Regress and Flat aperture trims for downlight cell are availble upon request	Universal - Non IC  AU	AWL Accent/Wall Wash Left  AWR Accent/Wall Wash Right  AWS Accent/Wall Wash Side  WAL Wall Wash Left/Accent  WAR Wall Wash Side/Accent  Note: Thumbnails are RCP view	Citizen  C14	24 2400K  27 2700K  30 3000K  35 3500K  40 4000K  Ambient Dim™  2722 * 2700-2200K *A14 Only  3019 3000-1900K  3022 * 3000-2200K *A14 Only  Tunable  TW1840 1800-4000K Tunable  White w/E1, E2, E3, E4  TW2765 2700-6500K Tunable White w/E1, E2, E3, E4  RG1280 1200-8000K RGBW Dynamic Color Changing *Requires E2 or E4	15 Spot  24 Narrow Flood  40 Flood  55 Wide Flood Note: Select for downlight cell only	C1 0-10 1.0%, UNV (120-277V) linear  C2 ELV/Triac 1.0%, (120V) linear  E1 0-10 0.1%, UNV (120-277V) log  E2 DALI-2 0.1%, UNV (120-277V) log  E3 0-10 0.1%, UNV (120-277V) linear  E4 ^ DMX 0.1%, UNV (120-277V) Universal DMX Driver/Controller RGBW-DMX ^ INCLUDES DMX/RDM COMPATIBLE DRIVER WITH BUILT-IN DECODER - CONTROLLER BY OTHERS Lutron  LD Digital Ecosystem 1.0%, UNV (120-277V) ECO Hi-Lume SoftOn/Fade-to-Black LDE1  LP Digital Ecosystem* 0.1%, UNV (120-277V) ECO Premier Hi-Lume SoftOn/Fade-to-Black LDE1  LP Digital Ecosystem* 0.1%, UNV (120-277V) ECO Premier Hi-Lume SoftOn/Fade-to-Black LDE1  LP Digital Ecosystem* 0.1%, UNV (120-277V) ECO Premier Hi-Lume SoftOn/Fade-to-Black LDE1  LP Digital Ecosystem* 0.1%, UNV (120-277V) ECO Premier Hi-Lume SoftOn/Fade-to-Black PEQ0, 20W max * Not compatible with C28	1C 1 Circuit 2C 2 Circuit	W White Paint  B Black Paint  D Wood*  PXX Specialty Paint Color*  P01-P15  C Custom/RAL Color**  *Refer to Wood Trim Guide ** Refer to Finish Guide  FINISH GUIDE LINK  WOOD TRIM GUIDE	Aperture Lens  91A Solite  93A Frosted  XXA Other Aperture Lens Treatments*  Reflector (lamp) Media  93L Frosted  91L Solite  97L Black Hexcel Louver  XXL Other reflector (lamp) media* 1 piece of Media per opening (aperture or reflector) can be selected *Refer to Lens Guide  LUSS ACCESSORVE LUNK  ACCESSORVE LUNK  REFER TO LENS ACCESSORVE LUNK  ACCESSORVE LUNK  REFER TO LENS ACCESSORVE  REFER TO L	EM Emergency Pack  CP Chicago Plenum  Controls  LR Lutron Wireless RF PowPak  ATH Lutron Athena Wireless Node Must be used with E2 driver  CA Casambi Wireless BLE to be paired with driver	



# Ceiling Cutouts and Dimensions






# Photometric Table

All data is based from goniometer measurements of production representative single cell fixture. Multiple heads will deliver additional light and will need to be accounted for individually in calculations. All lumen values can vary +/- 10% from LED manufacturer rated flux range. Measurements at 3000 CCT

SQUARE Beamspreads			15°				24°				40°				55°			
	Source	System watts (W)	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	Delivered Lumens (lm)	Lms/ Watt	Peak CD	10% Field
Open Regress Deep Regress	Citizen C14	15	1068	71	7642	42°	995	66	4174	46°	1037	69	3429	51°	996	66	1402	71°
	Citizen C20	21	1424	68	10190	40°	1326	63	5562	39°	1382	66	4570	55°	1328	63	1870	73°
	Citizen C28*	30	1848	62	13223	44°	1857	62	7791	47°	1916	64	6336	54°	1816	61	2556	69°
	Ambient Dim A14	15	694	46	6220	43°	656	44	3189	44°	656	44	1827	53°	643	43	1028	70°
	Citizen C14	15	1173	78	7776	42°	1091	73	4167	52°	1112	74	2422	66°	1058	71	1357	74°
	Citizen C20	21	1564	74	10369	41°	1455	69	5559	57°	1482	71	3199	63°	1411	67	1810	76°
	Citizen C28*	30	2158	72	14306	44°	2008	67	7669	55°	2045	68	4455	67°	1947	65	2496	72°
	Ambient Dim A14	15	810	54	5857	39°	779	52	3270	56°	779	52	1829	60°	764	51	1058	72°
(e)	Citizen C14	15	829	55	7740	37°	737	49	1436	46°	719	48	2379	51°	661	44	1357	64°
۱	Citizen C20	21	1105	53	10321	35°	982	47	5513	42°	958	46	3169	49°	881	42	1808	62°
Flat (Pin Hole)	Citizen CZ8*	30	1525	51	14258	32°	1355	45	7604	44°	1322	44	4375	53°	1216	41	2496	59°
	Ambient Dim A14	15	539	36	4828	36°	479	32	2326	42°	467	31	1301	50°	429	29	689	63°
	CCT Multiplier  CCT Citizen  2700 0.95		90 90 75			90 90 75 75			90 90 75				90 90 75					
3000 1.00		60 60			60 60			60				60						
35	3500 1.02		45 30 45			45 30 30			45 30 45				45 30 45					
40	4000 1.03		15 0 15			15 0 15			15 0 15				15 0 15					
	All measurements based on 3000 CCT.				'15.7°						39.8°				57°			


All Measurements delivered or derived delivered lumens based on 3000K. ISO CD plots based on Open Regress. Ambient dim at full output. C28 source requires active cooling and must be used with NIC housing. Flat (Pin Hole) at wider beam angles experience significant beam clipping - refer to PDF report for exact FWHM beam angle.



on a single head Core 4" square wall wash (CR4WW-SF). Multiple heads will deliver

easured at full output.\*C28 requires active cooling and NIC housing

more light and will need to be accounted for individually in calculations. Ambient Dim



Formerly known as 1240AW Recessed Adjustable Multiple Aperture (Cell)



# Color Data

All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated nominal flux. Measurements at 3000 CCT


## Citizen Sources for C14, 20 and C28



• 90+ CRI and RF

Spectra

• 60+R9, Hue Bin 1



## Ambient Dim 3000k to 1900k

- <3 MacAdam Ellipse (<3 SDCM)
- 95+ CRI and RF
- 90+R9, Hue Bin 1
- Follows Black Body Locus through dimming range

