


The GrazeFall Family

The GrazeFall family of premier linear wall grazers includes this surface mounted low glare baffle version. This high performance 2" (55mm) fixture is designed to highlight walls up to 15 feet high, featuring materials and revealing textures by contrasting light and shadow. The surface mounted housing can be mounted continuously and built to custom lengths in 6" increments with flush or regressed baffle positions. The narrow profile fixture is ideal suited to highlight the texture in surfaces such as stucco or brick, illuminate flat surfaces such as venetian plaster, wood, or specular surfaces such as polished stone or stainless steel. The 2" GrazeFall family has additional product offerings, including surface mounted lensed fixtures and an array of recessed options.



PROJECT: TYPE:
SPECIFIER: DATE:


Key Points (GZ2B-SM)

- Trim**
- Black or White baffle color options (Clear is available as a special request but not recommended for grazing application due to beam artifacts).
- Source Optics**
- Up to 345 lm/ft available in static white.
 - 90+ CRI and 60+ R9 for static white.
 - CCT offerings - 2700k, 3000k, 3500k and 4000k.
 - Dynamic tunable white in two ranges: 1800-4000k and 2700-6500k.
 - RGBW available with DMX control.
 - Veiling Acrylic lens standard - other lens types available.



- Housing**
- 15 color options + Custom or RAL# available.
 - Inside and outside "L" configurations are available for corners and wrap arounds.
 - Damp listed.
 - 2" specification increments (Integral Driver requires minimum of 2 feet).
 - Spring loaded snap in / snap out light engine for simple service.

- Driver And Control**
- 1% dimming standard - 0.1% available.
 - 0-10v, DALI, Lutron Ecosystem, EldoLED and DMX options available.
 - Flicker Free to IEEE 1789-2015.
 - Universal 120v to 277v.


Aperture Options



Flush Baffle (FB)
Formerly 811DB-LED-SH



Regress Baffle (RB)
Formerly 812-LED-SH



Specialty LINEAR Beamspreads			18° x 50°				Asymetric ISO CD Plot		
Lens Type	Source	System watts (W)	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	18° across width x 50° along run	CCT Multiplier	
Flush Baffle (BF)	SNL8	8	269	32	780	54°		2700	0.9
	SNL11	11	345	30	1008	54°		3000	1.00
Regress Baffle (RB)	SNL8	8	230	27	785	47°		3500	1.00
	SNL11	11	306	27	1042	47°			

All measurements delivered or derived delivered lumens at 3000K with black baffles. Values are per foot. ISO CD plot based on FB (Flush Baffle)

Ordering Codes

PROJECT:



SPECIFIER:

DATE:

TYPE:

QUANTITY:

Ordering Code Example: GZ2B-SM-FB-102"-SNL11-30-SY1-P24-B-79A


FIXTURE	APERTURE	LENGTH	SOURCE / WATTS	CCT	DRIVER / CONTROL	HOUSING FINISH	BAFFLE FINISH	LENS ACCESSORIES	ACCESSORIES
GZ2B-SM									
GrazeFall 2" Linear Baffled Wall Grazer - Surface Mount	FB Flush Baffle	— Specify total inches in 2" increments (minimum 24" length with integral driver)	SNL8 8W/ft 269Lm/ft** 90+CRI, 60+R9 Specialty Board*	27 2700K	SY1 0-10 1.0%, UNV (120-277V) linear	W White Paint 	W White - as molded 	Aperture Lens 79A Veiling Acrylic 91A Solite	IS9X Inside 90° Corner*
	RB Regressed Baffle		SNL11 11W/ft 345Lm/ft** 90+CRI, 60+R9 Specialty Board*	30 3000K	SY2 0-10 1.0%, UNV (120-277V) log	B Black Paint 	B Black as molded 		OS9X Outside 90° Corner*
			Tunable	35 3500K	E1 0-10 0.1%, UNV (120-277V) log	PXX Specialty Paint Color* 		Controls LR Lutron Wireless RF PowPak ATH Lutron Athena Wireless Node <i>Must be used with E2 driver</i> CA Casambi Wireless BLE to be paired with driver *X=specify number of corners	
			TWSL10 11W/ft 1300Lm/ft (source lumens at mid CCT range) 90+CRI, 60+R9 Specialty Tunable White Board +	40 4000K	E2 DALI-2 0.1%, UNV (120-277V) log	C Custom/RAL#* 			
			RGBWSL18 18W/ft 1000Lm/ft (source lumens) 90+CRI, 60+R9 Specialty RGBW Color Tunable Board ++	Tunable	E3 0-10 0.1%, UNV (120-277V) linear				
				1840 1800-4000K Tunable White	Lutron				
				2765 2700-6500K Tunable White	LD Digital Ecosystem* 1.0%, UNV (120-277V) ECO Hi-Lume SoftOn/Fade-to-Black LDE1				
				RGBW 1200-8000K Dynamic Color Changing	EldoLED				
					E22 0-10* 0.1%, UNV (120-277V) log 2 Channel for Tunable White				
					Tunable				
					RGBW-DMX DMX 0.1%, UNV (120-277V) Universal DMX Driver/Controller				

Ceiling Cutouts and Dimensions

To achieve best results, Specialty recommends to mount the fixture as close to the wall as possible. All drawings show closest possible mounting condition. Ceiling blocking is required and shown with a "X" in a box as a reference. Blocking will vary based on construction conditions and should be detailed on submittal drawings to define construction method and final wall offsets.


GZ2B- Surface Mount Flush Baffle

(GZ2B-SM-FB-)




GZ2B- Surface Mount Regressed Baffle

(GZ2B-SM-RB-)



Photometric Table

Values are either Lumens/foot or Watts/foot. All Measurements are delivered or derived delivered lumens based on 3000k and 12" length. All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated flux range. Measurements done with Black Baffle and Veiling Acrylic Lens (79A). Other lens selections will modify the lumen output and exact beam spread. If photometry is required with a specific lens treatment contact your regional sales manager for a special measurement. ISO CD Plot based on RB (Regressed Baffle). Recessed and Surface mount have same photometrics. Clear Aluminum Finish Baffles are available upon request but not recommended for wall grazing applications due to beam artifacts. If the wall material is "forgiving," the clear can be used.

Specialty LINEAR Beamspreads		18° x 50°					Asymetric ISO CD Plot	
Lens Type	Source	System watts (W)	Delivered Lumens (lm)	Lumens/ Watt	Peak CD	10% Field	18° across width x 50° along run	CCT Multiplier
Flush Baffle (BF)	SNL8	8	269	32	780	54°		2700 0.9
	SNL11	11	345	30	1008	54°		3000 1.00
Regress Baffle (RB)	SNL8	8	230	27	785	47°		3500 1.00
	SNL11	11	306	27	1042	47°		

Color Data

All data is based from goniometer measurements of production representative product. All data values can vary +/- 10% from LED manufacturer specified data range. Measurements at 3000 CCT unless otherwise noted.

SNL8 / SNL11

Specialty Linear Board

- <3 MacAdam Ellipse (<3 SDCM)
- 90+ CRI and RF
- 60+R9, Hue Bin 1 and 16

