



Drawings
coming
soon

PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (SCFP)

Housing

- Numerous Mounting options
- Finishes: Standard black and white
- Durable die-cast aluminum craftsmanship
- For use with A.A.G Stucchi surface and recessed track
- Accepts accessories (filters, GoBo, etc)

Source/Optics

- 360° horizontal rotation and 90° vertical aiming
- 90+ CRI standard
- 2 Different output options (10W and 30W)
- Beam Range 20° to 35°
- Precise, high definition built-in zoomable and shapeable projection
- IP20 

Driver And Control

- TruPhase™, 0-10v, DALI-2, DMX

PROJECT:

SPECIFIER:

DATE:

TYPE:

QUANTITY:

FIXTURE	MOUNTING	SOURCE / WATTS	CCT	BEAM	DRIVER / CONTROL	HEAD FINISH
SCFP						
Framing Projector	SM Surface Mount SMR Surface Mount * PM Panel Mount PMR* Panel Mount CM Canopy Mount <i>*Remote Driver</i> <i>For Track options see YSLH-SCFP</i>	10 10W 90+CRI, 60+R9 10 Watt 30 30W 90+CRI, 60+R9 30 Watt	27 2700K 30 3000K 35 3500K 40 4000K	20-35 Range	TD1 0-10V 2.0%, (120-277V) linear TD2 DALI-2 1.0%, (120-277V) linear TR2 TruPhase™ 0.1%, (100-277V) Up to 20W Forward and Reverse compatible Phase Dimming 2 Dimming Curves: Linear/Logarithmic Static White & Ambient Dim only	W White Paint  B Black Paint 