


# Scope Wonder

Ever wonder where light is coming from? Scope Wonder Downlight epitomizes this phenomena featuring super low UGR (glare) values. This fixture is designed not to be seen! The 3" offering provides an incredibly wide selection of finishes, mounting options and sources and technology including the release of our INK tunable white source in 2 dynamic ranges.



PROJECT:

TYPE:

SPECIFIER:

DATE:

## Key Points (SCW3D-R)

### Trim

- Machined aluminum Body in USA
- 4 trim bezel color options
- 40 flange color options + custom RAL
- Flanged or flangeless

### Source / Optics

- Tunable White with 2 available ranges (1800 to 4000K and 2700 to 6500K)
- UGR values <= 13 (considered excellent)
- Field changeable optics
- 3 beam spreads - 20°, 24° and 38°
- Up to 1664 delivered lumens
- <2 MacAdams Ellipses (<2 SDCM)
- 90+ CRI, 60+ R9 Standard; 95+ CRI, 90+ R9 available with Ambient Dim option
- 2400K, 2700K, 3000K, 3500K, 4000K Ambient Dim, RGBW & Tunable White options
- **TITLE 24** Source meets California Title 24 Requirements to JA8
- Lifetime: L87B3>55,000 hours at 40°C Ambient (for fixed white)

### Housing

- Remodel or millwork option available
- **TITLE 24** IC Rated / airtight housing approved for use in direct contact with insulation, Chicago Plenum Available and meets CA Title 24
- 2 pan options IC rated for use in direct contact with insulation (not for spray foam)

### Driver And Control

- Drivers are integral with fixtures unless noted as remote mount with \* in ordering code options. "K can" type drivers do not fit through the 3" hole and require remote mounting
- TruPhase™, 0-10, DALI-2, DMX, Ecosystem or Wireless Control
- Flicker free to IEEE 1789-2015 available with EldoLED and TruPhase™ selections
- Universal 120-277V

ROUND Beamspreads		20°						24°						36°					
Source	System watts (W)	Delivered Lumens (lm)	Lumens/Watt	UGR	Peak (fc)	10% Field	Delivered Lumens (lm)	Lumens/Watt	UGR	Peak (fc)	10% Field	Delivered Lumens (lm)	Lumens/Watt	UGR	Peak (fc)	10% Field			
Citizen C14	14	1198	86	11	7237	42°	1144	82	10	6031	44°	1174	84	11	3692	50°			
Citizen C20	21	1664	79	10	10186	42°	1581	75	12	8456	43°	1592	76	12	4756	50°			
Ambient Dim A14	15	836	56	12	6297	39°	789	53	12	4827	41°	797	53	12	2752	49°			
Tunable White - 1840	10	554	58	10	3247	42°	528	56	11	2638	44°	526	55	10	1563	50°			
Tunable White - 2765	10	746	79	10	4307	43°	697	73	12	3498	44°	708	75	13	1992	53°			

# Ordering Codes

## PROJECT:

**SPECIFIER:**

DATE:


TYPE:

**QUANTITY:**

*Ordering Code Example: SCW3D-R-Z-BP-A14-AD-36-E2-V01-A01*

Fixture	Trim	Mounting	Source / Watts	CCT	Beam	Driver / Control	Bezel Finish	Trim Finish	Accessories
SCW3D-R									
Scope Wonder 3" Downlight - Round	F Flanged Trim  Z Flangeless Trim  BP Bracket Pan (IC Rated) for mounting with hanger bars to studs or T-bar^  AT Airtight Housing*  PM Panel Mount §  RM Remodel mounts direct to ceiling - Wing Springs for flanged and drywall anchors for flangeless  CA CA Title 24 Compliant  * Chicago Plenum available with AT  ^ Not Airtight, Not for use with spray foam  § Must be used with flangeless trims.	NP New Pan (IC rated) for Mounting to bottom of studs^  15W 1233lm* 90+CRI, 60+R9  21W 1669lm* 90+CRI, 60+R9  Tunable  10W^ 90+CRI, 60+R9 Tunable White  21W 90+CRI, Tunable White  Ambient Dim™  15W 95+CRI,  21W 858lm 95+CRI, 90+R9  CA Title 24 Compliant  * Based on 20° Beam  **Based on 20° beam with 2765 CCT choice @ 4500K  ^ LTT or EldoLED Driver selection required and will be supplied with 2 channel version	Citizen  C14 15W 1233lm* 90+CRI, 60+R9  C20 21W 1669lm* 90+CRI, 60+R9  Tunable  T7 10W^ 90+CRI, 60+R9 Tunable White  T20 21W 90+CRI, Tunable White  Ambient Dim™  A14 15W 95+CRI,  A20 21W 858lm 95+CRI, 90+R9  CA Title 24 Compliant  * Based on 20° Beam  **Based on 20° beam with 2765 CCT choice @ 4500K  ^ LTT or EldoLED Driver selection required and will be supplied with 2 channel version	24 2400K  27 2700K  30 3000K  35 3500K  40 4000K  TW1840 1800-4000K Tunable White w/E1, E2, E3, E4  TW2765 2700-6500K Tunable White w/E1, E2, E3, E4  2722* 2700-2200K *A14 Only  3019 3000-1900K  3022 * 3000-2200K *A14 Only	20 Spot  24 Narrow Flood  36 Flood  40  TW1840 1800-4000K Tunable White w/E1, E2, E3, E4  TW2765 2700-6500K Tunable White w/E1, E2, E3, E4  2722* 2700-2200K *A14 Only  3019 3000-1900K  3022 * 3000-2200K *A14 Only	C1 0-10 1.0%, UNV (120-277V) linear  C2 ELV/Triac 1.0%, (120V) linear  E1 0-10* 0.1%, UNV (120-277V) log  E2 DALI-2* 0.1%, UNV (120-277V) log  E3 0-10* 0.1%, UNV (120-277V) linear  E4^ DMX 0.1%, UNV (120-277V) Universal DMX Driver/Controller RGBW-DMX  ^ INCLUDES DMX/RDM COMPATIBLE DRIVER WITH BUILT-IN DECODER - CONTROLLER BY OTHERS  L3 3 Wire or Ecosystem* 1.0%, (120-277V) Hi-Lume 3 Wire L3DA  TR2 TruPhase™ 0.1%, (120-120V) log Up to 20W Forward and Reverse compatible Phase Dimming Static White & Ambient Dim only  LD Digital Ecosystem* 1.0%, UNV (120-277V) ECO Hi-Lume SoftOn/Fade-to-Black LDE1  * Requires remote mounting	V01 Clear Metalize  V02 Black Metalize  V03 Champagne Metalize  V04 Gold Metalize  *See Finish Guide	A32 Clear Anodize  A01 Black Anodize  W White Paint  C Custom/RAL Color*  AXX Specialty anodize color*  A1-A36  PXX Specialty Paint Color*  P01-P15  K Blank for use with Flangeless or Panel Mount  *See Finish Guide	CP Chicago Plenum  EM Emergency Pack Controls  LR Lutron Wireless RF PowPak  ATH Lutron Athena Wireless Node Must be used with E2 driver (DALI-2)  CA Casambi Wireless BLE to be paired with driver  FINISH GUIDE LINK

# Fixture Details



Threaded collar comes integral with Pan. Receiver with integral trim flange threads into collar. Body assembly attaches to receiver with integral "J" hooks.

## Flanged Trim Option

Flanged Remodel uses wing springs (not shown) pg 5 for details.



Clear Flange Trim (A32) with Gold Bezel (V04) (shown)

## Flanged Finish Options



White  
P14



A01 Black  
Anodize



A32 Clear  
Anodize



A1-A36  
Anodized  
AXX



P01-P26  
Powder Coat  
PXX



Custom  
C

## Trim Bezel Finish Options



V01  
Clear Metalize



V02  
Black Metalize





V03  
Champagne Metalize



V04  
Gold Metalize

## Panel Trim Option


Panel Trim  
Mounting  
bracket must be  
attached to ceiling  
panel prior to  
ceiling installation



# Ceiling Cutouts and Dimensions


## Round New or Bracket Pan

(SCW3D-R-Z-BP / NP-)




## Round New or Bracket Pan

(SCW3D-R-F-BP / NP-)




## Round Panel Mount

(SCW3D-R-Z-PM-)



## Panel Mount Detail


(SCW3D-R-Z-PM-)



## Ceiling Cutouts and Dimensions

### Round Remodel


(SCW3D-R-Z-RM-)



### Flangeless Trim (Z)

### Driver Enclosure


for C1, C2, TR2



### Round Remodel


(SCW3D-R-F-RM-)

### Flanged Trim (F)




### Driver Enclosure

for E1, E2, E3, E4, LD



### Round Airtight (AT)





# Mounting Options

## New Pan

(SCW3D-R\_-NP)

For new construction and attachment to bottom of studs





## Bracket Pan



(SCW3D-R\_-BP)

For new construction using hanger bars for attaching to studs or drop ceiling

Option 1- Attaching to Studs






Option 2- Attaching to Drop Ceiling



For Panel Mounting to Millwork See Page 3 and installation instructions. For Remodel and Housing mounting see page 4

# Photometric Table


All data below are delivered lumens based on goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated flux range.

ROUND Beamspreads		20°						24°						36°					
Source	System watts (W)	Delivered Lumens (lm)	Lumens/ Watt	UGR	Peak (fc)	10% Field	Delivered Lumens (lm)	Lumens/ Watt	UGR	Peak (fc)	10% Field	Delivered Lumens (lm)	Lumens/ Watt	UGR	Peak (fc)	10% Field			
Citizen C14	14	1198	86	11	7237	42°	1144	82	10	6031	44°	1174	84	11	3692	50°			
Citizen C20	21	1664	79	10	10186	42°	1581	75	12	8456	43°	1592	76	12	4756	50°			
Ambient Dim A14	15	836	56	12	6297	39°	789	53	12	4827	41°	797	53	12	2752	49°			
Tunable White - 1840	10	554	58	10	3247	42°	528	56	11	2638	44°	526	55	10	1563	50°			
Tunable White - 2765	10	746	79	10	4307	43°	697	73	12	3498	44°	708	75	13	1992	53°			
CCT Multiplier		Beam angle						Beam angle						Beam angle					
CCT	Citizen	Beam angle						Beam angle						Beam angle					
2700	0.95	 20.3°						 23.3°						 36°					
3000	1.00																		
3500	1.02																		
4000	1.03																		
All measurements are delivered lumens based on 3000K unless otherwise noted below. Ambient Dim measured at full output. Tunable White measurements at mid-point CCT of range (2700K for 1840 and 4500K for 2765 source). UGR values based on 4H 3H row.																			

## Color Data



### Citizen Source C14, C20

- <2 MacAdam Ellipse (<2 SDCM)
- 90+ CRI and RF
- 60+R9, Hue Bin 1



### Ambient Dim Source A14 (AD - 3000k to 1900k)


- <3 MacAdam Ellipse (<3 SDCM)
- 95+ CRI and RF
- 90+R9, Hue Bin 1
- Follows Black Body Locus through dimming range



## Tunable White source T7 - CCT 1840 (1800k to 4000k)

- <3 MacAdam Ellipse (<3 SDCM)
- 94 CRI average across all CCTs
- 76 R9 average across all CCTs
- Available with wired or wireless control

Spectral Power Distributions at all listed CCTs available upon request




1800K




Color Temp	TUNABLE WHITE - 1800-4000K						
	1800	2200	2500	2700	3000	3500	4000
System Watts	10	10	10	10	10	10	10
Delivered Lumens	428	488	528	554	608	644	644
Luminaire Efficiency	45	51	56	58	64	68	68


Flux and Color data based on 20° measurement at 2700K.  
All other values are extrapolated from actual and analytical tests



3000K




4000K




## Tunable White source T7 - CCT 2765 (2700k to 6500k)

- <3 MacAdam Ellipse (<3 SDCM)
- 94 CRI average across all CCTs
- 96 R9 average across all CCTs
- Available with wired or wireless control

Spectral Power Distributions at all listed CCTs available upon request




2700K




Color Temp	TUNABLE WHITE - 2700-6500K								
	2700	3000	3500	4000	4500	5000	5500	6000	6500
System Watts	10	10	10	10	10	10	10	10	10
Delivered Lumens	657	723	746	747	746	745	744	742	750
Luminaire Efficiency	69	76	79	79	79	78	78	78	79

Flux and Color data based on 20° measurement at 4500K.  
All other values are extrapolated from actual and analytical tests



5000K



6500K

