


The Slice Family

The Slice Combo pairs a diffuse general source with a punchy, directional downlight in a single fixture. As part of the Slice family, it is offered in linear 1" and 2" wide profiles in recessed, surface and pendant options. This 1" recessed fixture combines the Multicell and Lensed fixtures to allow an almost infinite number of design options. We have defined a series of standard offerings within this datasheet, but expect that you will want to modify the configurations for your project needs. Please take heed of the design criteria for minimum sizes. For more detail on the lens or multicell sections please refer to the datasheets (SL1DC-LFRC or SL1DC-MCFRC). The Slice Combo can be used to illuminate your space with precision.



Lumens and Length of 5 Cell Module											
2" Slice		Length		SO6 (6 Watt System)				SO11 (11 Watt System)			
Modules	Cells	US (in)	Metric (mm)	Delivered Lm			System Watts	Delivered Lm			System Watts
				15°	30°	45°		15°	30°	45°	
1	5	5	136	493	542	523	6	669	749	736	11
Lumens per Foot for lensed sections											
2" Linear Lensed		Performance/Foot									
Source		System Watts (W/ft)	Delivered Lumens (lm/ft)		Lumens/Watt (ft)			Peak cd			
F4		5	317		66			125			
F8		10	633		66			215			

PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (SL1DC-CBRC)

Source / Optics

- Lensed - Even illumination with wide (~100°) lambertian distribution.
- Lensed - Even illumination with wide (~100°) lambertian distribution.
- Multicell - Up to 1700 Lumens/foot
- 3 beam spreads - 15°, 30° and 45°
- 57/63+ lumens per watt/foot (multicell/lensed respectively).
- Multicell - Ultra low glare with UGR values <10.
- <3 MacAdam Steps (<3 SDCM).
- CCT offerings - 2700k, 3000k, 3500k and 4000k.
- 90+ CRI and 50+ R9
- title 24 Supports CA Title 24 part 6 compliance meeting JA8 requirements

Housing

- 14 available housing finishes+ custom/RAL available for flanged trims.
- Profile allows continuous runs to your desired length. thorough combinations of general illumination modules with multicell down lights using three building blocks: lensed downlights, multicell downlights and the optional made to length blank panels, for separation between modules and fillers to allow fabrication to exact lengths.
- Lengths longer than 8' are assembled in the field with engineered joiners
- IP65 Damp listed

Driver And Control

- Universal 120v to 277v.
- Remote driver mounting required.
- 0.1% dimming available in 0-10 or DALI-2 protocols.
- Flicker Free to IEEE 1789-2015 (low risk to no risk).
- Universal 120v to 277v.

Ordering Codes

PROJECT:

SPECIFIER:

DATE:

TYPE:

QUANTITY:

Ordering Code Example: SL1DC-CBRC-AF-8A-SO11/F8-30-45-SY1-WH






Fixture	Mounting	Configuration	Source / Watts	CCT	Beam	Driver / Control	Housing Finish	Accessories
SL1DC-CBRC	Flanged Housings AF   Flanged Airtight/IC	4A 4ft (nominal) 5 cell ends - 3' lens center 5A 5ft (nominal) 5 cell ends - 4' lens center 6A 6ft (nominal) 5 cell ends - 5' lens center 8A 8ft (nominal) 5 cell ends - 7' lens center 8B 8ft (nominal) 5 cell ends and center - two 3' lens sections CST Custom Submit sketch/ dwg of desired configuration and fixture length. 10 cell minimum for Multicell. 1ft minimum for lens section. 3ft minimum overall length. Insert any blank lengths as desired. Refer to Slice 1" Multicell and Lens datasheets for more information. Lengths > 96" are shipped in 96" sections and assembled with engineered joiner	Lens F4 5W 703Lm 90+CRI, 50+R9 values per foot F8 10W 1363Lm 90+CRI, 50+R9 values per foot Multicell SO6   12W/ft * 876Lm/ft * 90+CRI, 50+R9 Specialty Board SO11   22W/ft 1714Lm/ft * 90+CRI, 50+R9 Specialty Board	27 2700K 30 3000K 35 3500K 40 4000K	15 Spot 30 Narrow Flood 45 Flood	SY1 0-10 1.0%, UNV (120-277V) linear SY2 0-10* 1.0%, UNV (120-277V) log EldoLED E1 0-10 0.1%, UNV (120-277V) log E2 DALI-2 0.1%, UNV (120-277V) log E3 0-10 0.1%, UNV (120-277V) linear	Standard B Black Paint  Optional W White Paint  PXX Specialty Paint Color*  P01-P15	EM Emergency Pack CP Chicago Plenum

Fixture Lengths and Design Criteria

Standard and Custom

Standard defined lengths and configurations are shown below. Using the basic building blocks of celled modules, lensed modules and blank panels, custom continuous runs are available using the following design criteria: minimum of two 5 cell modules at any location within a specified run; minimum 1ft length of lensed section at any location within a specified run; blank panels of any length greater than 1/2" permitted; and minimum overall length > 3ft.

SL1DC-CBRC - Standard Modular Configurations (5 cell runs)




Ceiling Cutouts and Dimensions

SL1DC-CBRC - Recessed Flanged


AF

(SL1DC-CBRC-AF)




Remote Driver Enclosure

REMOTE MOUNTING REQUIRED



REMOTE MOUNTING REQUIRED



* Note: Small driver enclosures is for use with a pair of 5 cell multicell units. For quantities greater than two 5 cell multicell units, the larger enclosure is used. Larger enclosure is used for lensed sections.


Photometric Table

Values are delivered lumens based on a 5-cell module at 5.21" (5 1/4") (132.5mm) and extrapolated for per foot numbers or 1 foot of lensed section.
CAUTION: IES FILES ARE FOR A 5 CELL MODULE. CALCULATIONS MUST PLACE THE 5 CELL MODULE FILE 5.21" (132.5mm) ON CENTER OR 1 FOOT LENSED SECTION AT THE APPROPRIATE LOCATION OF THE DEFINED CONFIGURATION. All data is based on goniometer measurements of production representative product. Measurements are taken at 3000 CCT with a black baffle and can vary +/- 10% from LED manufacturer rated flux range.


Slice 1" Multicell Linear Downlight - S06 (6 Watt System)						
1" Slice		Length		Delivered Lumens		
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	98.5	109	104.8
1	5	5	136	493	542	523
2	10	11	271	985	1090	1048
3	15	16	407	1478	1635	1572

CCT Multiplier

CCT	Citizen
2700	0.95
3000	1.00
3500	1.05
4000	1.1



Slice 1" Multicell Linear Downlight - S011 (11 Watt System)						
1" Slice		Length		Delivered Lumens		
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	133.7	147.6	146.7
1	5	5	136	669	749	736
2	10	11	271	1337	1476	1467
3	15	16	407	2006	2214	2201




Lumens per Foot for lensed sections						
2" Linear Lensed		Performance/Foot				
Source	System Watts (W/ft)	Delivered Lumens (lm/ft)	Lumens/Watt (ft)	Peak cd		
F4	5	317	66	125		
F8	10	633	66	215		

CCT Multiplier

CCT	Citizen
2700	0.96
3000	1.00
3500	1.03
4000	1.04

ISO CD plot based on F8 source.





Color Data

SO6 & SO11


SO6 - 15°




Spectra




CRI: 90.4 (R1-R8)




Color distortion



TM30: 91.5




TM-30Color




SO6 - 30°




Spectra




CRI: 90.0 (R1-R8)




Color distortion



TM30: 91.3



TM-30Color




SO6 & SO11


SO6 - 45°







Spectra



CRI: 90.3 (R1-R8)





Color distortion




SO11 - 15°






Spectra



CRI: 90.0 (R1-R8)



Color distortion





SO6 & SO11


SO11 - 30°

89
CRI47
R991
RF98
RG


Spectra




CRI: 89.6 (R1-R8)




Color distortion



TM30: 91.1





TM-30Color




SO11 - 45°

90
CRI48
R991
RF97
RG

Spectra




CRI: 89.9 (R1-R8)



Color distortion



TM30: 91.3



TM-30Color

