




The Slice Family

Illuminate your space with precision Slices of glare free light. The Slice family offers linear 1" and 2" wide profiles in recessed and surface options. The 1" surface delivers over 1700 lumens per foot with a modular design allowing continuous light of 1" square cells to your specified length. The unobtrusive fixture features incredibly low glare values (UGR) ≥10. With multiple CCTs, 2 outputs and 3 beam options, the slice 1" packs a bunch in a small footprint.




PROJECT: TYPE:
SPECIFIER: DATE:

Key Points (SL1DC-MCFSF)


Trim

- 1" cells arrayed in 5 cell increments up to your specified length
- 14 available housing finishes+ custom/RAL available

Source / Optics

- Up to 1700 Lumens/foot
- 3 beam spreads - 15°, 30° and 45°
- 60+ lumens per watt/foot
- Ultra low glare with UGR values <10
- <3 MacAdam Steps (<3 SDCM)
- CCT offerings - 2700k, 3000k, 3500k
- 90+ CRI and 50+ R9
-  Supports CA Title 24 part 6 compliance meeting JA8 requirements
- Lifetime: L70B50>55,000 hours at 40°C Ambient

Housing

- Lengths longer than 8' are assembled in the field with engineered joiners
- Profile allows continuous light from 5 1/4" to your desired length in 5 cell increments.
-  Damp listed

Driver And Control







- Remote driver mounting required
- 0.1% dimming availalbe in 0-10 or DALI-2 protocols
- Flicker Free to IEEE 1789-2015 (low risk to no risk)
- Universal 120v to 277v

Slice 1" Multicell Linear Downlight - SO6 (6 Watt System)						
1" Slice		Length		Delivered Lumens		
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	98.5	109	104.8
1	5	5	136	493	542	523
2	10	11	271	985	1090	1048
3	15	16	407	1478	1635	1572
Slice 1" Multicell Linear Downlight - SO11 (11 Watt System)						
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	133.7	147.6	146.7
1	5	5	136	669	749	736
2	10	11	271	1337	1476	1467
3	15	16	407	2006	2214	2201

Ordering Codes

PROJECT: SPECIFIER:
DATE: TYPE: QUANTITY:

Ordering Code Example: SL1DC-MCFSF-SM-30-SO13-30-45-SY1-P16


FIXTURE	MOUNTING	CELLS	SOURCE / WATTS	CCT	BEAM	DRIVER / CONTROL	HOUSING FINISH
SL1DC-MCFSF							
Slice 1" Continuous Linear Surface Multicell Downlight	SM Surface Mount	5 5 3/8" (136.5mm)	SO6 ●● 6W/ft 1635Lm/ft* 90+CRI, 50+R9 Specialty Board	27 2700K	15 Spot	SY1 0-10 1.0%, UNV (120-277V) linear	Standard
		10 10 9/16" (269mm)		30 3000K	30 Narrow Flood	SY2 0-10* 1.0%, UNV (120-277V) log	B Black Paint 
		15 15 13/16" (401.5mm)	SO11 ●● 11W/ft 2217Lm/ft* 90+CRI, 50+R9 Specialty Board	35 3500K	45 Flood	EldoLED	Optional
		20 21" (534mm)				E1 0-10 0.1%, UNV (120-277V) log	W White Paint 
		25 26 1/4" (666.5mm)	*Delivered Lumens based on tests performed at 3000K w/ 30° beam angle			E2 DALI-2 0.1%, UNV (120-277V) log	PXX Specialty Paint Color* 
		30 31 7/16 (799mm)	●● Supports CA T24 part 6 compliance meeting JA8 requirements			E3 0-10 0.1%, UNV (120-277V) linear	C Custom/RAL* 
		35 36 11/16" (931.5mm)				*Log dimming curve available on >=15 cell selection	Note: Baffle is black only *See Finish Guide
		40 41 7/8" (1064mm)				Note: Remote driver required for all fixture lengths. See Electrical Guide for wire run distances	
		-- specify total # of cells in 5 cell increments if over 40 cells^					
		^ Lengths > 96" are shipped in 96" sections and assembled with engineered joiner					

Fixture Lengths

Standard lengths are shown below. Longer continuous runs are available. Simply specify the total number of cells, in 5 cell increments, for lengths longer than 40 cells. Fixture length = number of 5 cell modules x 132.5mm (module length) + 4mm for end caps.

SL1DC- Standard Modular Configurations (5 cell runs)

(SL1DC-MCFSF)




Ceiling Cutouts and Dimensions

For lengths over 40 cells a submittal drawing is required.

SL1DC- Surface Mount Multicell Housing







SM

(SL1DC-MCFSF-)



Photometric Table

Values and files shown are based on delivered lumens and system watts for a 5-cell module at 5.25" (133 mm). Data for 10-cell and 15-cell modules can be approximated by multiplying by 2 or 3, respectively. All data is based on goniometer measurements of production-representative product at 3000K CCT with a black baffle, and may vary by ±10% from the LED manufacturer's rated flux range.

Slice 1" Multicell Linear Downlight - S06 (6 Watt System)						
1" Slice		Length		Delivered Lumens		
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	98.5	109	104.8
1	5	5	136	493	542	523
2	10	11	271	985	1090	1048
3	15	16	407	1478	1635	1572
CCT Multiplier						
CCT	Citizen					
2700	0.95					
3000	1.00					
3500	1.05					
4000	1.1					
Slice 1" Multicell Linear Downlight - S011 (11 Watt System)						
1" Slice		Length		Delivered Lumens		
Modules	Cells	US (in)	Metric (mm)	15°	30°	45°
N/A	1	1.1	27.1	133.7	147.6	146.7
1	5	5	136	669	749	736
2	10	11	271	1337	1476	1467
3	15	16	407	2006	2214	2201
						

Color Data

All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated data range. Measurements at 3000 CCT unless otherwise noted.

SO6 & SO11


SO6 - 15°

90
CRI

50
R9

91
RF

97
RG




SO6 - 30°

90
CRI

48
R9

91
RF

98
RG



SO6 & SO11





SO6 - 45°

90
CRI

50
R9

91
RF

99
RG








SO11 - 15°

90
CRI

48
R9

91
RF

97
RG



SO6 & SO11

SO11 - 30°


89
CRI

47
R9


91
RF

98
RG




Spectra



CRI: 89.6 (R1-R8)



Color distortion



SO11 - 45°


90
CRI

48
R9


91
RF

97
RG

Spectra



CRI: 89.9 (R1-R8)



Color distortion

