



The Slice Family - Wall Wash

Illuminate your space with precision Slices of glare free light. The Slice family offers linear 2" profiles in recessed and below ceiling options. The 2" Surface/Pendant delivers over 900 lumens per 3 cell modules, with a modular design allowing continuous light of 2" square cells to your specified length (in 3 cell increments). Offered in flanged, flangeless and multiple CCTs.



PROJECT:

TYPE:

SPECIFIER:

DATE:

Key Points (SL2DW-MCRC)

Source / Optics

- Up to 900 Lumens/foot
- S08 & SO15 Title 24 compliant to JA8
- 46+ lumens per watt/foot
- <3 MacAdam Steps (<3 SDCM)
- CCT offerings - 2700k, 3000k, 3500k
- 90+ CRI and 70+ R9
- Lifetime: L70B50>55,000 hours at 40°C Ambient

Housing

- 14 available housing finishes+ custom/RAL available
- Flanged or Flangeless
- Profile allows continuous light from 3 cells to your desired length in 3 cell increments.
- Lengths longer than 48 cells (95 5/16" [2421mm]) are assembled in the field with supplied joiners
- Damp listed

Driver And Control

- dimming down to 0.1% - 120v
- Integral Driver in selections > 9 cells
- 0-10 or DALI-2 protocols
- Flicker Free to IEEE 1789-2015
- Universal 120v to 277v

Ordering Codes

PROJECT: SPECIFIER:
DATE: TYPE: QUANTITY:









Ordering Code Example: SL2DW-MCRC-AF-B-48-SO15-30-45-SY1-P16

FIXTURE	MOUNTING	LENGTH	CELLS	CONFIGURATION	SOURCE / WATTS	CCT	BEAM	DRIVER / CONTROL	BEZEL FINISH	HOUSING FINISH
SL2DW-MCRC										
Slice 2" Continuous Linear Recessed Multicell Wall Wash	AF Flanged Airtight IC Rated AP * Airtight Plaster IC-Rated Title 24 Compliant to JA8	- Specify Length of Stem or Cable in inches Lengths > 48 cells (95 5/16"[2421mm]) are finalized upon submittal approval	3 ^ 6 3/16"" (157mm) 6 ^ 12 1/18" (308mm) 12 24" (610mm) 18 35 7/8" (912mm) 24 47 13/16" (1214mm) 30 59 11/16" (1515mm) 36 71 9/16" (1817mm) 42 83 7/16" (2119mm) 48 95 5/16" (2421mm) ___ Custom Specify total # of cells in 3 cell increments *6 Cell increments shown above *Available in 3 cell increments When ordering > 48 cells (95 5/16"[2421mm]) + 5 15/16" per 3 cell increment(s) Lengths > 48 cells are shipped in 48 cell sections and field assembled with engineered joiner(s) ^Remote Driver Required	STD Standard Code for standard continuous configuration CST Custom Code for adding blank spaces or lensed elements. See configuration page for guidance. Submittal dwgs required	SO8 8W/ft 404Lm/ft* 103+CRI, 72+R9 SO15 16W/ft 716Lm/ft* 94+CRI, 69+R9 SO20 21W/ft 900Lm 90+CRI, 69+R9 * California Title 24 compliant to JA8	27 2700K 30 3000K 35 3500K	WW Wall Wash	SY1 0-10 1.0%, UNV (120-277V) linear SY2 0-10 1.0%, UNV (120-277V) log E1 0-10 0.1%, UNV (120-277V) log E2 DALI-2 0.1%, UNV (120-277V) log E3 0-10 0.1%, UNV (120-277V) linear TR2 TruPhase™ 0.1%, (120-120V) log Up to 20W Forward and Reverse compatible Phase Dimming Static White & Ambient Dim only • Note: Remote Driver required for 3 & 6 cell selections • Integral Driver for > 6 cell selections	V01 Clear Metalize V02 Black Metalize V03 Champagne Metalize V04 Gold Metalize B Black Paint W White Paint 	Standard B Black Paint Optional W White Paint PXX Specialty Paint Color* P01-P15 C Custom/RAL* Note: Baffle is black only *See Finish Guide


Fixture Lengths

Standard lengths are shown below. Use Custom ordering code for your desired length in 3 cell increments. *For lengths > 48 cells (95 5/16" [2421mm]) a submittal drawing is required.

Standard Modular Configurations (6 cell runs)
(SL2DW-MCRC-)



Remote Driver Box for 3 Cell & 6 Cell Selections




Ceiling Cutouts and Dimensions

Recessed Mount Multicell Housing

/AP


(SL2DW-MCRC-AP-)




Recessed Mount Multicell Housing

/AF

(SL2DW-MCRC-AF-)



Photometric Table Values are delivered lumens based on a 6-cell module at 12"[305mm] nominal (not including end plates - see Fixture Lengths page for dimensions) and extrapolated for per foot numbers. CAUTION: IES FILES ARE FOR A 6 CELL MODULE. CALCULATIONS MUST PLACE THE 6 CELL MODULE FILE 12" [305mm] nominal ON CENTER FOR THE ENTIRE SPECIFIED LENGTH OF FIXTURE. All data is based on goniometer measurements of production representative product. Measurements are taken at 3000 CCT with a black baffle and can vary +/- 10% from LED manufacturer rated flux range.

Lumens per 6 Cell module							
Source	System watts (W)	Delivered Lumens (lm/ft)	Lumens/ Watt/ft	Peak (cd)	CRI	R9	10% Field
SO8	8	404	51	371	95	72	105°
SO15	16	716	47	661	94	69	105°
SO20	20	882	44	795	94	69	106°
CCT Multiplier							
CCT	Citizen						
2700	0.95						
3000	1.00						
3500	1.05						
4000	1.1						







SO8 Color Data • <3 MacAdam Ellipse (<3 SDCM)

95
CRI

72
R9

91
RF

99
RG




Color Data


All data is based from goniometer measurements of production representative product. All lumen values can vary +/- 10% from LED manufacturer rated data range. Measurements at 3000 CCT unless otherwise noted.

SO8 and SO15

SO15 Color Data • <3 MacAdam Ellipse (<3 SDCM)



SO20 Color Data • <3 MacAdam Ellipse (<3 SDCM)



All color data is based on goniometer measurement of production representative product optic.
Information includes on board primary optics and diffusing lens.
All colors values can vary +/- 10% from LED manufacturer rated data range.