specialty lighting industries

Light efficiency:

56 Lumen/Watt

Light quality:

CRI: 97.5


Output: 1120 lm

Peak: 5015 cd

Power: 20.0 W



Beam angle



Test number:
CR3D-RA-DR-AD20-3018-15°

Luminaire Model:


Date:
7/15/2026

LUM: 1120


2984 K

***Variation due to source size, bezel geometry, or secondary optics**

Spectra



CRI: 97.5 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color diviation from black body
	CRI	CRI R9	TM30 R_f	TM30 R_g	CQS	x	y	u	v	Δuv
	97.5	97.9	94.6	100.9	95.9	0.437	0.402	0.252	0.347	-0.0007

specialty lighting industries


TM-30Color

R_f 94.6


Fidelity index R_f

R_g 100.9


Gammut index R_g




		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	96	0%	1%
2	97	1%	-1%
3	96	0%	-1%
4	94	-4%	-3%
5	96	-3%	1%
6	97	0%	2%
7	93	-2%	4%
8	97	1%	1%
9	94	1%	3%
10	92	2%	5%
11	92	4%	5%
12	93	4%	0%
13	95	1%	-3%
14	94	3%	-3%
15	94	-1%	1%
16	91	2%	-7%




Color vector graphics





Color distortion






www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.

specialty lighting industries

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
5015lx	1254lx	557lx	313lx	201lx	139lx	102lx	78lx	62lx	50lx	41lx	35lx	30lx	26lx	22lx	20lx	17lx	15lx	14lx	13lx
465.9fc	116.5fc	51.8fcd	29.1fcd	18.6fcd	12.9fcd	9.5fcd	7.3fcd	5.8fcd	4.7fcd	3.9fcd	3.2fcd	2.8fcd	2.4fcd	2.1fcd	1.8fcd	1.6fcd	1.4fcd	1.3fcd	1.2fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5015	5015	4637	4220	3681	3048	2437	1905	1373	1050	759	554	425	309	247	186	150	118	93	75
100%	100%	92%	84%	73%	61%	49%	38%	27%	21%	15%	11%	8%	6%	5%	4%	3%	2%	2%	1%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5015	5015	4637	4220	3681	3048	2437	1905	1373	1050	759	554	425	309	247	186	150	118	93	75
100%	100%	92%	84%	73%	61%	49%	38%	27%	21%	15%	11%	8%	6%	5%	4%	3%	2%	2%	1%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5015	5015	4637	4220	3681	3048	2437	1905	1373	1050	759	554	425	309	247	186	150	118	93	75
100%	100%	92%	84%	73%	61%	49%	38%	27%	21%	15%	11%	8%	6%	5%	4%	3%	2%	2%	1%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5015	5015	4637	4220	3681	3048	2437	1905	1373	1050	759	554	425	309	247	186	150	118	93	75
100%	100%	92%	84%	73%	61%	49%	38%	27%	21%	15%	11%	8%	6%	5%	4%	3%	2%	2%	1%


Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
23.5°	**45.6°**	**67.1°**	**98.6%**	**96.9%**

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.

specialty lighting industries

Light planning

Luminaire budgetary diagram



Luminaire budgetary diagram

AREA m2 (area of the room)

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)				Room Values are expressed as percentage of Lumens delivered to the task surface													
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	112	110	108	112	110	108	107	106	105	103	102	101	100	99	98	97	96
2	110	106	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92
3	107	102	98	95	105	100	97	94	98	95	92	95	93	91	93	91	90	88
4	103	97	93	90	101	96	92	89	94	91	88	92	89	87	90	88	86	85
5	100	93	89	86	98	92	88	85	91	87	85	89	86	84	88	85	83	82
6	96	90	85	82	95	89	85	82	88	84	81	86	83	81	85	83	80	79
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77
8	91	84	79	76	90	83	79	76	82	79	76	81	78	76	81	78	75	74
9	88	81	77	74	87	81	77	74	80	76	74	79	76	73	78	75	73	72
10	86	79	75	72	85	78	74	72	78	74	71	77	74	71	76	73	71	70

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
383 lm	446 lm	173 lm	67.6 lm	25.4 lm	9.56 lm	6.45 lm	4.89 lm	3.94 lm

90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

 As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.