

Light efficiency:

62 Lumen/Watt

Output: 1052 lm

Light quality:


CRI: 96.0

Peak: 1283 cd

Power: 16.8 W

No photo

Beam angle



Test number:

CR4D-RA-OR-Z-T15-TW1840-50

Luminaire Model:

CORE 4" ROUND OPEN REGRESS T15-1840-50°

Date and time:

8/20/2025 3:34:30 PM

LUM: 1052


Primary Optic 50° = 57.1°

2838 K


Measured at Mid-Point of Tuneable White CCT Range

*Variation due to source size, bezel geometry, or secondary optics

Spectra



CRI: 96.0 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
	CRI	CRI R9	TM30 R _f	TM30 R _g	CQS	x	y	u	v	Δuv
	96.0	81.8	93.6	103.3	92.6	0.441	0.391	0.259	0.345	-0.0056

R_f 93.6


Fidelity index R_f

R_g 103.3


Gammut index R_g

TM30: 93.6



TM-30Color




Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	95	-2%	0%
2	95	-1%	2%
3	92	1%	4%
4	94	1%	2%
5	95	3%	2%
6	93	5%	0%
7	95	2%	-2%
8	95	2%	-2%
9	97	0%	0%
10	96	1%	2%
11	92	2%	5%
12	91	5%	0%
13	92	4%	-5%
14	90	5%	-7%
15	95	0%	-3%
16	88	0%	-9%




Color vector graphics



Color distortion




Hue bin



Color Evaluation Sample

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1283lx	321lx	143lx	80lx	51lx	36lx	26lx	20lx	16lx	13lx	11lx	9lx	8lx	7lx	6lx	5lx	4lx	4lx	4lx	3lx
119.2fcd	29.8fcd	13.2fcd	7.4fcd	4.8fcd	3.3fcd	2.4fcd	1.9fcd	1.5fcd	1.2fcd	1fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1283	1283	1273	1257	1236	1210	1179	1142	1098	1046	986	919	844	761	670	569	466	367	281	209
100%	100%	99%	98%	96%	94%	92%	89%	86%	81%	77%	72%	66%	59%	52%	44%	36%	29%	22%	16%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1283	1283	1273	1257	1236	1210	1179	1142	1098	1046	986	919	844	761	670	569	466	367	281	209
100%	100%	99%	98%	96%	94%	92%	89%	86%	81%	77%	72%	66%	59%	52%	44%	36%	29%	22%	16%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1283	1283	1273	1257	1236	1210	1179	1142	1098	1046	986	919	844	761	670	569	466	367	281	209
100%	100%	99%	98%	96%	94%	92%	89%	86%	81%	77%	72%	66%	59%	52%	44%	36%	29%	22%	16%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1283	1283	1273	1257	1236	1210	1179	1142	1098	1046	986	919	844	761	670	569	466	367	281	209
100%	100%	99%	98%	96%	94%	92%	89%	86%	81%	77%	72%	66%	59%	52%	44%	36%	29%	22%	16%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
57.1°	81.5°	90.2°	98.8%	97.8%

LAMPS (number of lamps)
50

Light planning Luminaire budgetary diagram



Luminaire budgetary diagram AREA m2 (area of the room) Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93	95	93	91	93	91	89	87
3	103	97	92	88	101	95	91	87	93	89	86	90	87	84	88	85	83	82
4	98	90	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76
5	93	85	79	75	92	84	79	75	82	78	74	81	77	73	79	76	73	71
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	70	66	83	75	69	65	74	69	65	72	68	65	71	67	64	63
8	81	71	65	61	79	71	65	61	70	65	61	69	64	61	68	64	61	59
9	77	67	62	58	76	67	61	58	66	61	58	65	61	57	64	60	57	56
10	73	64	58	55	72	64	58	54	63	58	54	62	57	54	61	57	54	53

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
119 lm	312 lm	361 lm	205 lm	36.6 lm	4.79 lm	5.07 lm	4.51 lm	3.13 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.