

Light efficiency:

77 Lumen/Watt

Output: 760 lm

Light quality:


CRI: 96.2

Peak: 1878 cd

Power: 9.8 W



Beam angle



Test number:

CR4D-RA-OR-Z-T9-TW1840-36

Luminaire Model:

CORE 4" ROUND OPEN REGRESS T9-1840-36°

Date and time:

8/21/2025 4:03:40 PM

LUM: 760


Primary Optic 36° = 36.9°

2880 K


Measured at Mid-Point of Tuneable White CCT Range

*Variation due to source size, bezel geometry, or secondary optics

Spectra



CRI: 96.2 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
	CRI	CRI R9	TM30 R _f	TM30 R _g	CQS	x	y	u	v	Δuv
	96.2	83.8	93.9	103.1	93.1	0.438	0.391	0.257	0.344	-0.0053

R_f 93.9


Fidelity index R_f

R_g 103.1


Gammut index R_g

TM30: 93.9


TM-30Color




Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	96	-2%	0%
2	96	-1%	2%
3	92	1%	4%
4	95	0%	1%
5	95	2%	2%
6	93	4%	0%
7	95	1%	-1%
8	96	2%	-2%
9	97	1%	1%
10	95	1%	3%
11	92	3%	5%
12	91	5%	0%
13	92	3%	-5%
14	90	5%	-7%
15	95	0%	-3%
16	88	0%	-9%




Color vector graphics



Color distortion




Hue bin



Color Evaluation Sample

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1878lx	469lx	209lx	117lx	75lx	52lx	38lx	29lx	23lx	19lx	16lx	13lx	11lx	10lx	8lx	7lx	6lx	6lx	5lx	5lx
174.4fcd	43.6fcd	19.4fcd	10.9fcd	7fcd	4.8fcd	3.6fcd	2.7fcd	2.2fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1878	1868	1842	1793	1723	1622	1494	1342	1168	980	791	619	467	341	243	170	118	83	57	39
100%	100%	98%	96%	92%	86%	80%	71%	62%	52%	42%	33%	25%	18%	13%	9%	6%	4%	3%	2%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1878	1868	1842	1793	1723	1622	1494	1342	1168	980	791	619	467	341	243	170	118	83	57	39
100%	100%	98%	96%	92%	86%	80%	71%	62%	52%	42%	33%	25%	18%	13%	9%	6%	4%	3%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1878	1868	1842	1793	1723	1622	1494	1342	1168	980	791	619	467	341	243	170	118	83	57	39
100%	100%	98%	96%	92%	86%	80%	71%	62%	52%	42%	33%	25%	18%	13%	9%	6%	4%	3%	2%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1878	1868	1842	1793	1723	1622	1494	1342	1168	980	791	619	467	341	243	170	118	83	57	39
100%	100%	98%	96%	92%	86%	80%	71%	62%	52%	42%	33%	25%	18%	13%	9%	6%	4%	3%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
36.9°	58.9°	73.9°	99.0%	98.4%

LAMPS (number of lamps)
50

Light planning Luminaire budgetary diagram



Luminaire budgetary diagram AREA m2 (area of the room) Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	106	102	100	108	104	101	98	101	98	96	98	96	94	95	94	92	91
3	106	100	96	93	104	99	95	92	97	93	91	94	92	89	92	90	88	87
4	102	96	91	88	100	95	90	87	93	89	86	91	88	85	89	86	84	83
5	98	91	87	83	97	90	86	83	89	85	82	87	84	81	86	83	81	79
6	95	87	83	79	93	87	82	79	85	81	78	84	81	78	83	80	77	76
7	91	84	79	76	90	83	79	75	82	78	75	81	77	75	80	77	74	73
8	88	81	76	72	87	80	75	72	79	75	72	78	74	72	77	74	71	70
9	85	77	73	70	84	77	73	69	76	72	69	75	72	69	75	71	69	68
10	82	75	70	67	81	74	70	67	74	69	67	73	69	66	72	69	66	65

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
167 lm	338 lm	189 lm	47.4 lm	7.84 lm	2.45 lm	2.48 lm	2.77 lm	2.65 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.