

Light efficiency:

38 Lumen/Watt


Output: 314 lm

Light quality:


CRI: 96.2

Peak: 667 cd

Power: 8.2 W



Beam angle



Test number:

CR4D-SA-FL-Z-T9-TW1840-50

Luminaire Model:

Core 4" Square Flat T9-1840-50°

Date and time:

8/26/2025 1:33:47 PM


LUM: 314

Primary Optic = 40°


2862 K

Measured at Mid-Point of Tuneable White CCT Range
*Variation due to source size, bezel geometry, or secondary optics

Spectra



CRI: 96.2 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
	CRI	CRI R9	TM30 R _f	TM30 R _g	CQS	x	y	u	v	Δuv
	96.2	84.0	93.9	102.8	93.3	0.440	0.392	0.257	0.345	-0.0050

R_f 93.9


Fidelity index R_f

R_g 102.8


Gammut index R_g

TM30: 93.9


TM-30Color





Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	96	-2%	0%
2	96	-1%	2%
3	93	1%	3%
4	95	0%	1%
5	95	1%	2%
6	94	4%	0%
7	94	1%	-1%
8	96	2%	-1%
9	97	1%	1%
10	95	1%	3%
11	92	3%	5%
12	91	5%	0%
13	92	3%	-5%
14	90	4%	-7%
15	95	0%	-2%
16	88	0%	-10%




Color vector graphics



Color distortion




Hue bin



Color Evaluation Sample

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
667lx	167lx	74lx	42lx	27lx	19lx	14lx	10lx	8lx	7lx	6lx	5lx	4lx	3lx	3lx	3lx	2lx	2lx	2lx	2lx
61.9fcd	15.5fcd	6.9fcd	3.9fcd	2.5fcd	1.7fcd	1.3fcd	1fcd	0.8fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd	0.2fcd	0.2fcd	0.2fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
667	663	655	642	623	595	555	506	449	389	333	284	238	191	133	74	32	10	2	2
100%	99%	98%	96%	93%	89%	83%	76%	67%	58%	50%	43%	36%	29%	20%	11%	5%	1%	0%	0%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
667	663	655	642	623	595	555	506	449	389	333	284	238	191	133	74	32	10	2	2
100%	99%	98%	96%	93%	89%	83%	76%	67%	58%	50%	43%	36%	29%	20%	11%	5%	1%	0%	0%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
667	663	655	642	623	595	555	506	449	389	333	284	238	191	133	74	32	10	2	2
100%	99%	98%	96%	93%	89%	83%	76%	67%	58%	50%	43%	36%	29%	20%	11%	5%	1%	0%	0%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
667	663	655	642	623	595	555	506	449	389	333	284	238	191	133	74	32	10	2	2
100%	99%	98%	96%	93%	89%	83%	76%	67%	58%	50%	43%	36%	29%	20%	11%	5%	1%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
40°	60.5°	65.7°	95.0%	93.3%

LAMPS (number of lamps)
50

Light planning Luminaire budgetary diagram



Luminaire budgetary diagram AREA m2 (area of the room) Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	104	100	97	106	102	99	96	99	96	93	96	94	91	93	91	90	88
3	104	98	93	90	102	97	92	89	94	90	88	92	89	86	89	87	85	83
4	100	93	88	84	98	92	87	84	90	86	83	88	84	82	86	83	81	79
5	96	88	83	79	94	88	83	79	86	82	78	84	81	78	83	80	77	76
6	92	84	79	76	91	84	79	75	82	78	75	81	77	74	80	76	74	73
7	89	81	76	72	88	80	75	72	79	75	71	78	74	71	77	73	71	69
8	86	77	72	69	85	77	72	69	76	72	68	75	71	68	74	71	68	67
9	83	74	69	66	82	74	69	66	73	69	66	72	68	65	71	68	65	64
10	80	72	67	63	79	71	66	63	70	66	63	70	66	63	69	65	63	62

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
60.3 lm	130 lm	93.1 lm	8.61 lm	2.00 lm	3.99 lm	6.02 lm	5.95 lm	3.69 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.