

Light efficiency:

74 Lumen/Watt


Output: 607 lm

Light quality:


CRI: 96.0

Peak: 2495 cd

Power: 8.2 W



Beam angle



Test number:

CR4D-SA-OR-Z-T9-TW1840-24

Luminaire Model:

Core 4" Square Open Regress T9-1840-24°

Date and time:

8/26/2025 1:39:50 PM

LUM: 607


Primary Optic = 26.6°

2911 K


Measured at Mid-Point of Tuneable White CCT Range

*Variation due to source size, bezel geometry, or secondary optics

Spectra



CRI: 96.0 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
	CRI	CRI R9	TM30 R _f	TM30 R _g	CQS	x	y	u	v	Δuv
	96.0	87.2	94.1	103.0	93.8	0.435	0.390	0.256	0.344	-0.0054

R_f 94.1


Fidelity index R_f

R_g 103.0


Gammut index R_g

TM30: 94.1



TM-30Color



Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	96	-2%	0%
2	96	0%	1%
3	94	1%	3%
4	95	0%	0%
5	95	1%	2%
6	94	4%	0%
7	94	1%	0%
8	96	2%	-1%
9	97	1%	1%
10	95	1%	3%
11	92	3%	5%
12	91	5%	0%
13	93	3%	-5%
14	90	4%	-6%
15	95	0%	-2%
16	88	1%	-9%




Color vector graphics



Color distortion




Hue bin



Color Evaluation Sample

Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2495lx	624lx	277lx	156lx	100lx	69lx	51lx	39lx	31lx	25lx	21lx	17lx	15lx	13lx	11lx	10lx	9lx	8lx	7lx	6lx
231.8fc	57.9fcd	25.8fcd	14.5fcd	9.3fcd	6.4fcd	4.7fcd	3.6fcd	2.9fcd	2.3fcd	1.9fcd	1.6fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2495	2472	2372	2202	1976	1715	1435	1153	890	662	485	351	252	180	127	88	57	36	22	12
100%	99%	95%	88%	79%	69%	58%	46%	36%	27%	19%	14%	10%	7%	5%	4%	2%	1%	1%	0%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2495	2472	2372	2202	1976	1715	1435	1153	890	662	485	351	252	180	127	88	57	36	22	12
100%	99%	95%	88%	79%	69%	58%	46%	36%	27%	19%	14%	10%	7%	5%	4%	2%	1%	1%	0%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2495	2472	2372	2202	1976	1715	1435	1153	890	662	485	351	252	180	127	88	57	36	22	12
100%	99%	95%	88%	79%	69%	58%	46%	36%	27%	19%	14%	10%	7%	5%	4%	2%	1%	1%	0%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2495	2472	2372	2202	1976	1715	1435	1153	890	662	485	351	252	180	127	88	57	36	22	12
100%	99%	95%	88%	79%	69%	58%	46%	36%	27%	19%	14%	10%	7%	5%	4%	2%	1%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
26.6°	48.1°	63.3°	99.4%	99.1%

LAMPS (number of lamps)
50

Light planning Luminaire budgetary diagram



Luminaire budgetary diagram AREA m2 (area of the room) Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio)																	
	Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	111	109	107	107	105	104	103	102	101	100	99	98	96
2	111	107	104	102	109	106	103	101	103	100	98	100	98	96	97	96	94	93
3	107	103	99	96	106	101	98	95	99	96	94	97	94	92	94	93	91	90
4	104	99	95	91	102	98	94	91	96	92	90	94	91	89	92	90	88	87
5	101	95	91	88	100	94	90	87	92	89	87	91	88	86	90	87	85	84
6	98	92	87	84	97	91	87	84	90	86	84	88	85	83	87	85	82	81
7	95	89	84	81	94	88	84	81	87	83	81	86	83	80	85	82	80	79
8	92	86	82	79	91	85	81	79	84	81	78	83	80	78	83	80	78	77
9	90	83	79	76	89	83	79	76	82	78	76	81	78	76	81	78	75	75
10	88	81	77	74	87	80	77	74	80	76	74	79	76	74	79	76	73	73

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
201 lm	276 lm	104 lm	20.6 lm	1.40 lm	0.877 lm	1.07 lm	1.32 lm	1.53 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.