

Light efficiency:

75 Lumen/Watt


Output: 523 lm

Light quality:


CRI: 90.3

Peak: 1138 cd

Power: 7.0 W



Beam angle



Test number:

SL1-SO6-30K-45°

Luminaire Model:

Slice 1" Standard Output SO6-30K-45°

Date and time:


8/13/2025 9:15:55 AM

LUM: 523


3027 K

*Variation due to source size, bezel geometry, or secondary optics

Spectra



CRI: 90.3 (R1-R8)



Color parameters

	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
	CRI	CRI R9	TM30 R _f	TM30 R _g	CQS	x	y	u	v	Δuv
	90.3	50.0	91.5	97.9	89.8	0.440	0.413	0.249	0.350	0.0030

R_f 91.5


Fidelity index R_f

R_g 97.9


Gammut index R_g

TM30: 91.5


TM-30Color




Hue Bin	R_f	Graphic shifts (%)	
		Chroma	Hue
1	89	-6%	-1%
2	91	-4%	3%
3	89	-2%	5%
4	94	0%	3%
5	95	-1%	3%
6	97	1%	0%
7	94	-2%	-3%
8	97	-2%	0%
9	94	-3%	2%
10	89	-3%	5%
11	88	0%	9%
12	90	4%	2%
13	93	3%	-4%
14	88	4%	-9%
15	88	-1%	-7%
16	86	-3%	-10%




Color vector graphics




Color distortion



Hue bin



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1138lx	284lx	126lx	71lx	46lx	32lx	23lx	18lx	14lx	11lx	9lx	8lx	7lx	6lx	5lx	4lx	4lx	4lx	3lx	3lx
105.7fc	26.4fcd	11.7fcd	6.6fcd	4.2fcd	2.9fcd	2.2fcd	1.7fcd	1.3fcd	1.1fcd	0.9fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.3fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1138	1138	1127	1104	1070	1021	953	872	781	682	581	481	382	285	195	124	82	54	33	18
100%	100%	99%	97%	94%	90%	84%	77%	69%	60%	51%	42%	34%	25%	17%	11%	7%	5%	3%	2%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1138	1138	1127	1104	1070	1021	953	872	781	682	581	481	382	285	195	124	82	54	33	18
100%	100%	99%	97%	94%	90%	84%	77%	69%	60%	51%	42%	34%	25%	17%	11%	7%	5%	3%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1138	1138	1127	1104	1070	1021	953	872	781	682	581	481	382	285	195	124	82	54	33	18
100%	100%	99%	97%	94%	90%	84%	77%	69%	60%	51%	42%	34%	25%	17%	11%	7%	5%	3%	2%


Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1138	1138	1127	1104	1070	1021	953	872	781	682	581	481	382	285	195	124	82	54	33	18
100%	100%	99%	97%	94%	90%	84%	77%	69%	60%	51%	42%	34%	25%	17%	11%	7%	5%	3%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
40.5°	60.9°	73.1°	98.6%	97.7%

LAMPS (number of lamps)
50

Light planning Luminaire budgetary diagram



Luminaire budgetary diagram AREA m² (area of the room) Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	109	107	112	110	108	106	105	104	102	102	101	99	98	97	97	95
2	110	105	102	99	107	104	100	98	100	98	96	98	95	94	95	93	92	90
3	105	100	96	92	103	98	95	91	96	93	90	94	91	89	91	89	87	86
4	101	95	90	87	100	94	89	86	92	88	85	90	87	84	88	85	83	82
5	97	90	86	82	96	90	85	82	88	84	81	86	83	80	85	82	80	78
6	94	86	81	78	92	86	81	78	84	80	77	83	79	77	82	79	76	75
7	90	83	78	74	89	82	77	74	81	77	74	80	76	73	79	75	73	72
8	87	79	74	71	86	79	74	71	78	74	71	77	73	70	76	73	70	69
9	84	76	71	68	83	76	71	68	75	71	68	74	70	67	73	70	67	66
10	81	73	68	65	80	73	68	65	72	68	65	71	68	65	71	67	65	64

Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
104 lm	225 lm	150 lm	30.0 lm	5.00 lm	2.97 lm	2.43 lm	2.43 lm	2.45 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm	0.000 lm

www.specialty-lighting.com As a result of our continuous improvement, values are subject to change without notice. These are delivered results and can vary +/- 10% from published source data range.